

D

Е

F

G

Н

Κ

L

M

CONTENTS

ACCELERATOR CONTROL SYSTEM2	SERVICE DATA AND SPECIFICATIONS (SDS) 3
Removal and Installation2	Accelerator Control3
REMOVAL2	PEDAL TRAVEL3
INSTALLATION2	

Revision: July 2005 ACC-1 2005 Maxima

ACCELERATOR CONTROL SYSTEM


ACCELERATOR CONTROL SYSTEM

PFP:18005

Removal and Installation REMOVAL

EBS00JTF

- 1. Disconnect the negative battery cable.
- 2. Disconnect the accelerator position sensor electrical connector.
- a. Pull the connector lock back to unlock the connector from the accelerator pedal position sensor as shown.
- b. Pull up on the connector to disconnect it from the accelerator pedal position sensor as shown.



- 3. Remove the upper accelerator pedal nuts and lower accelerator pedal bolt.
- 4. Remove the accelerator pedal and accelerator position sensor assembly.
 - For electrical inspection of the accelerator pedal position sensor, refer to <u>EC-642</u>, "ACCELERATOR PEDAL POSITION SENSOR".



- Do not disassemble the pedal assembly. Do not remove the accelerator pedal position sensor from the pedal assembly.
- Avoid impact from dropping during handling.
- Keep the pedal assembly away from water.


INSTALLATION

- 1. Installation is in the reverse order of removal.
 - Check the accelerator pedal for smooth operation. There should be no binding or sticking when applying or releasing the accelerator pedal.
 - Check that the accelerator pedal moves through the full specified distance of pedal travel.

Pedal travel A : 52.6 - 58.2 mm (2.07 - 2.29 in)



When the harness connector of the accelerator pedal position sensor is disconnected, perform the "Accelerator pedal released position learning". Refer to EC-90, "Accelerator Pedal Released Position Learning".



SERVICE DATA AND SPECIFICATIONS (SDS)

SERVICE DATA AND SPECIFICATIONS (SDS)

PFP:00030

Accelerator Control PEDAL TRAVEL

EBS00JTG

Accelerator control pedal - total travel	52.6 - 58.2 mm (2.07 - 2.29 in)

ACC

Α

С

D

Е

F

G

Н

K

L

M

SERVICE DATA AND SPECIFICATIONS (SDS)