

Specification	displayMate™	edge® 4111	Soloist™ 4111
Digital Video Out - DVI-I Out	Yes	Yes	Yes
Component YUV/RGB Video Out, BNC Jack	Yes-Optional Cable	Yes-Optional Cable	Yes-Optional Cable
DVI-D Out	Yes-Optional Cable	Yes-Optional Cable	Yes-Optional Cable
VGA Out	Yes-Optional Cable	Yes-Optional Cable	Yes-Optional Cable
Composite Video (Analog), BNC connector	Yes-Connection on Chassis	Yes-Connection on Chassis	Yes- Media Cable Included
S-Video Out	No	No	Yes-Media Cable Included
Unbalanced Stereo Analog Audio Out	L/R RCA jack	L/R RCA jack	1/8" female jack
S/PDIF Audio Out , RCA jack	No	YES-Connection on Chassis	Yes- Media Cable Included
FireWire	No	No	Yes-Reserved for future use
Parallel Port	YES	YES	YES
USB 2.0 Host	No	No	Yes-Reserved for future use
Maximum Decode:	25Mbps	25Mbps	40Mbps
110-240 AC Line Input (Power)	No	Yes	Yes
External 12 volt Power Supply	Yes included	Yes - Option	No
Connection Kit: Power cord, serial adapter, Ethernet cord	Yes	Yes	Yes
Serial Port: Control via a Telnet Client using Adtec Command API (ex. Tera Term)	Yes - Labeled COM 1	Yes - Labeled COM 1	Yes- Labeled RS-232
Terminal Monitor: (For Diagnostics Only)	Yes - Labeled COM 2	Yes - Labeled COM 2	Yes- Labeled Terminal Monitor
Ethernet – 10/100 Base –T, RJ-45 connector	Yes	Yes	Yes
Ethernet – GIG-E, RJ-45 connector	No	No	Yes – Speeds Content Transfer
Hard drive	4GB (3.5GB usable) or 8GB (7.5GB usable) Compact Flash	80GB (2.5 inch)	300GB (3.5 inch)
Capacity for SD @ 5Mbps	1.5 hrs or 3 hrs	35 hrs	133 hrs
Capacity for HD @ 25Mbps	18 minutes or 40 minutes	7 hrs	26 hrs
Size	1.265" tall, 5.7" wide, 10.5" deep	1 RU tall, 8.5" wide, 10.5" deep,	1 RU tall, 19" wide, 10" deep
Rack Mountable	Yes: 3 in one RU space with optional Adtec Shelf or optional displayEnvelope	Yes: 2 in one RU space with optional Adtec Shelf	Yes – 1 RU Chassis Rack Mount Included