



SpitFire15

- _15-watt RMS digital guitar amplifier with 8" speaker
- _Uses GuitarFX technology
- _80 programs, each a factory preset that can be edited or restored to factory default
- _9 effects modules, each with multiple selectable effects
- _Over 40 different effects, allowing for innumerable effects combinations
- _Built-in auto-chromatic tuner



SpitFire30

- _30-watt RMS digital guitar amplifier with 10" speaker
- _Uses GuitarFX technology
- _Separate drive control for quick tone manipulation
- _80 programs, each a factory preset that can be edited or restored to factory default
- _9 effects modules, each with multiple selectable effects
- _Over 40 different effects, allowing for innumerable effects combinations
- _Built-in auto-chromatic tuner



SpitFire60

- _60-watt RMS digital guitar amplifier with 8" speaker
- _Uses GuitarFX technology
- _Separate drive, bass, and treble controls for quick tone manipulation
- _80 programs, each a factory preset that can be edited or restored to factory default
- _9 effects modules, each with multiple selectable effects
- _Over 40 different effects, allowing for innumerable effects combinations
- _Built-in auto-chromatic tuner



ProLinear 720

- _Bi-amplified studio reference monitor
- _4th order active crossover
- _80 watts (LF) / 40 watts (HF)
- _7" woven Kevlar woofer
- _1" silk dome tweeter
- _Balanced 1/4" and XLR inputs



ProLinear 720DSP

- _Bi-amplified studio reference monitor
- _Built-in digital crossover and 4-band parametric EQ with 8 pre-sets and 8 user defined settings
- _24-bit/48kHz processing
- _Serial interface allows PC control of up to 16 speakers
- _80 watts (LF) / 40 watts (HF)
- _7" woven Kevlar woofer
- _1" silk dome tweeter



ProLinear 820

- _Bi-amplified studio reference monitor
- _4th order active crossover
- _80 watts (LF) / 40 watts (HF)
- _8" woven Kevlar woofer
- _1" silk dome tweeter
- _Balanced 1/4" and XLR inputs



ProLinear 820DSP

- _Bi-amplified studio reference monitor
- _Built-in digital crossover and 4-band parametric EQ with 8 pre-sets and 8 user defined settings
- _24-bit/48kHz processing
- _Serial interface allows PC control of up to 16 speakers
- _80 watts (LF) / 40 watts (HF)
- _8" woven Kevlar woofer
- _1" silk dome tweeter

MultiMix16FXD

- _16-input, 4-buss mixer with onboard digital effects and digital output
- _8 microphone/line inputs with up to 50dB of preamp gain
- _4 stereo line inputs
- _Internal digital effects processor with 100 preset effects
- _3-band EQ per channel
- _1 pre/post-fader aux send per channel (switchable)
- _1 post-fader aux send/effects send per channel
- _S/PDIF output



Zone Mix6

- _6 line, 1 phono, 3 mic inputs
- _Balanced mic inputs on front and rear panels
- _Mic 1 equipped with auto ducking, sensitivity adjustment, gain, and EQ controls
- _Easy front panel on/off switch for all inputs
- _Dual zone assign for all inputs
- _2 zone outputs with gain, pan, EQ, and stereo/mono adjustment
- _Both zones equipped with unbalanced and balanced outputs with master gain reduction
- _Removable knobs with tamper resistant plugs available
- _Headphone output with volume control



PowerTrip8

- _1U power conditioner and light module
- _8 separate AC power jacks with switch
- _Large AC voltage display
- _Two light bars with dimmer and switch
- _Surge and transient protection



ProActive 2.0

- _6" 2-way active monitor
- _65 watt power amplifier (45WLF, 20W HF)
- _Active crossover
- _1/4" input connector
- _Input level potentiometer
- _Internal 110/220V power supply





AirFX/AirSynth In-Store Dealer Display

- _Auto demo display
- _CD player included
- _No assembly required
- _See rep for buy-in program details

ModFX In-Store Dealer Display

- _Auto demo display
- _CD player included
- _No assembly required
- _See rep for buy-in program details

