

**M1Active MK2****Product Description**

By combining our expertise in reference monitor design with our proven track record in studio amplification, Alesis' new M1 Active™ Bi-amplified Reference Monitor offers the incredibly accurate response that perfectly translates to every playback system. Its internal active crossover and custom-designed dual amplifiers ensure an extremely consistent performance under a variety of different studio conditions and program material. The result is a broad, extremely flat frequency response, clear imaging with a wide sweet spot, high power handling and detailed high- and mid-frequency response that only a professional powered monitor can deliver.

With the lineage of our TEC Award winning Monitor One Studio Reference Monitor, Alesis speakers have already become a standard in project and professional studios around the world. If you're looking for the same great accuracy and detailed response in a powered system that's truly affordable, the answer is clear: the new M1 Active from Alesis.

**Key Features & Benefits****Low Frequency Driver:**

6.5" non-woven carbon fiber with Santoprene surround and dual magnet shielded configuration

**High Frequency Driver:**

1" silk dome with medium viscosity ferrofluid coolant and dual magnet shielded configuration

**Crossover:**

1500Hz, 8th-order, 48dB/octave filters

**Input Impedance:**

20k<sub>Ω</sub> balanced,  
10k<sub>Ω</sub> unbalanced

**Frequency Range:**

38 Hz - 23.5 kHz (-10dB point)

**Connectors:**

Combination XLR-1/4" jack with input level control

**Dimensions & Weight**

**Dimensions:** 8.5"x15"x9.75"(WxHxD)  
(381mm x 216mm x 248mm)

**Weight:** 19.5 lbs. (8.9kg) each