CABLES

MS8108CA – 15ft

5 BNC Male to 13W3 Male Cable for use with all SUN and SGI computers

The Universal input cable has 12 position dip-switches that allow the user to set pin-outs on the cable for compatibility with all Sun Workstations output currently available. Sun Workstations can operate in both RGBS mode or in RGBHV mode.

Computer Type	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10	SW11	SW12
SUN	V. Sync		ID 2			C. Sync	ID 0	H. Sync			ID 1	ID 0
Sun and Sun Ultra (Composite Sync)	OFF	OFF	OFF	OFF	OFF	**ON**	OFF	OFF	OFF	OFF	OFF	OFF
Sun Ultra and Sun Voyager (HV Sync)	**ON**	OFF	OFF	OFF	OFF	OFF	OFF	**ON**	OFF	OFF	OFF	OFF
Modes of operation												
No Monitor	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF
Reserved (640x480)	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	**ON**
ECD (1024x768)	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	**ON**	OFF
Apple (1152x900)	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	**ON**	**ON**
Sun Standard (1152x900) 66Hz	OFF	OFF	**ON**	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF
GPD (1280x1024)	OFF	OFF	**ON**	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	**ON**
Sun (1152x900) 76Hz	OFF	OFF	**ON**	OFF	OFF	OFF	OFF	OFF	OFF	OFF	**ON**	OFF
Reserved	OFF	OFF	**ON**	OFF	OFF	OFF	OFF	OFF	OFF	OFF	**ON**	**ON**
SGI	ID 3	ID 0		H. Sync	C. Sync		V. Sync		ID 1	ID 2	GRD	GRD
GS out from SGI	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	**ON**	**ON**
Comp. Sync output from SGI	OFF	OFF	OFF	OFF	**ON**	OFF	OFF	OFF	OFF	OFF	**ON**	**ON**
HV Sync out from SGI	OFF	OFF	OFF	**ON**	OFF	OFF	**ON**	OFF	OFF	OFF	**ON**	**ON**

ALTINEX

SIGNAL MANAGEMENT SOLUTIONS