## **MS8110CA – 15ft**

## 5 BNC Male to 13W3 Male Cable

The 13W3 Male to 5 BNC Male cable has 12 position dip-switches that allow the user to set pin-outs on the cable for compatibility with Sun Workstations Type 3 Output, IBM Power Output, and SGI output.

Computer Type	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10	SW11	SW12
SUN			ID 2			ID 1	ID 0	GND		C. Sync		
Sun Workstation Type 3 (Composite Sync)	OFF	OFF	OFF	OFF	OFF	OFF	OFF	ON	OFF	ON	OFF	OFF
Modes of operation												
No Monitor	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF
Reserved (640x480)	OFF	OFF	OFF	OFF	OFF	OFF	ON	OFF	OFF	OFF	OFF	OFF
ECD (1024x768)	OFF	OFF	OFF	OFF	OFF	ON	OFF	OFF	OFF	OFF	OFF	OFF
(1152x900) 76Hz, 19"	OFF	OFF	OFF	OFF	OFF	ON	<mark>ON</mark>	OFF	OFF	OFF	OFF	OFF
Sun Standard (1152x900) 66Hz	OFF	OFF	ON	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF
GPD (1280x1024)	OFF	OFF	ON	OFF	OFF	OFF	ON	OFF	OFF	OFF	OFF	OFF
Sun (1152x900) 76Hz	OFF	OFF	ON ON	OFF	OFF	ON	OFF	OFF	OFF	OFF	OFF	OFF
Reserved	OFF	OFF	<u>2</u>	OFF	OFF	ON	07	OFF	OFF	OFF	OFF	OFF
IBM Power PC	ID 2	ID 3	SELF TEST	ID 0	ID 1	N/C	V. Sync	GND	GND	H. Sync		
RGBHV	OFF	OFF	OFF	OFF	OFF	OFF	ON	ON	OFF	ON		
SGI	ID 3	ID 0		ID 1	ID 2	GRD			H. Sync		V. Sync	C. Sync
Sync On Green	OFF	OFF	OFF	OFF	OFF	ON	OFF	OFF	OFF	OFF	OFF	OFF
Comp. Sync	OFF	OFF	OFF	OFF	OFF	ON	OFF	OFF	OFF	OFF	OFF	ON
HV Sync	OFF	OFF	OFF	ON	OFF	ON	OFF	OFF	ON	OFF	ON	OFF

These cables have a 13W3 "D" male connector with 12 DIP switches on one end and a 15-pin "HD" VGA type male connector on the other end.



