
MATERIAL SAFETY DATA SHEET

=====
 | SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION |
 =====

PRODUCT NAME : FOAMTAK 363 HI STR FAST TACK ADH
 IDENTIFICATION NUMBER: FCA363 DATE PRINTED: 08/18/97
 PRODUCT USE/CLASS :

DISTRIBUTED BY:
 AURALEX ACOUSTICS, INC.
 8851 N. HAGUE RD.
 INDIANAPOLIS, IN 46256-1284

EMERGENCY TELEPHONE: 800-424-9300
 24 HOUR EMERGENCY PHONE

PREPARER: JLM, PREPARE DATE: 08/18/97
 REPLACES DATE: 07/10/95 *JLM 8/19/97*

=====
 | SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS |
 =====

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT % LESS THAN
01	HEXANE	110-54-3	35.0 %
02	PROPANE	74-98-6	20.0 %
03	ACETONE	67-64-1	20.0 %
04	DIMETHYL ETHER	115-10-6	15.0 %

ITEM	EXPOSURE LIMITS					
	TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL-CEILING	COMPANY TLV-TWA	SKIN
01	NO INFO	NO INFO	500 ppm	NO INFO	NO INFO	NO
02	NO INFO	NO INFO	1000 ppm	NO INFO	NO INFO	NO
03	NO INFO	1000 ppm	1000 ppm	NO INFO	NONE	NO
04	NO INFO	NO INFO	NO INFO	NO INFO	1000 ppm	NO

(See Section 16 for abbreviation legend)

=====
 | SECTION 3 - HAZARDS IDENTIFICATION |
 =====

*** EMERGENCY OVERVIEW ***: KEEP FROM REACH OF CHILDREN. DO NOT PUNCTURE, INCINERATE, OR PLACE AEROSOL PRODUCT CONTAINERS IN COMPACTORS. CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED SINCE CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID, AND/OR SOLID). ALL HAZARD PRECAUTIONS GIVEN MUST BE OBSERVED. DO NOT FLAME CUT, BRAZE, OR USE WELDING TORCH. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THIS PRODUCT MAY BE HARMFUL OR FATAL.

SECTION 15 - REGULATORY INFORMATION

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

: ON JUNE 30, 1993 THE OSHA Z-1-A TABLE WAS REVOKED AND OSHA REVERTED BACK TO THEIR PRIOR EXPOSURE LIMITS. THE VALUES ON THIS MSDS REFLECT THE ROLL BACK TO THE PRIOR VALUES. SOME STATES MAY CONTINUE TO ENFORCE THE 1993 LIMITS. ON JUNE 16, 1995 EPA ANNOUNCED IN A FINAL RULE THAT ACETONE WOULD NO LONGER BE CONSIDERED A VOC FOR AIR ATTAINMENT STANDARDS. (IT IS NOW AN EXEMPT COMPOUND) NOT ALL STATES HAVE ADOPTED THE EXEMPT STATUS OF ACETONE AT THIS TIME. THE VOC CALCULATIONS ON THIS MSDS ARE BASED ON ACETONE BEING AN EXEMPT COMPOUND. THE JUNE 16 RULE ALSO REMOVED ACETONE FROM THE LIST OF SARA 313 REPORTABLE CHEMICALS, EFFECTIVE THE 1994 REPORTING YEAR.

SECTION 16 - OTHER INFORMATION

HMIS RATINGS - HEALTH: 2 FLAMMABILITY: 4 REACTIVITY: 1

PREVIOUS MSDS REVISION DATE: 07/10/95

REASON FOR REVISION: NEW FORMAT

VOLATILE BY WEIGHT: 82.3% VOLATILE BY VOLUME: 87.7%

VOC CONTENT: 64.6 % BY WEIGHT, 443 GRAMS/LITER TOTAL PRODUCT, 524 GRAMS/LITER LESS WATER AND EXEMPT, 0.70 LBS/CAN

LEGEND: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

:

=====

The information contained on this MSDS is been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations. The environmental information and hazardous materials identification system have been included by the distributor in order to provide additional health and hazard classification information. The ratings recommend are based upon the criteria supplied by the developers of these rating systems, together with the distributor's interpretation of the available data. Proper personal protective equipment varies widely with conditions of use and anticipated exposure. We recommend that a supervisor or other qualified person determine proper PPE for intended use.

<END OF MSDS>