

Multican (HA4) 4-Channel Headphone Amplifier The Australian Monitor Installation Series HA4 is a high quality, low price 4channel stereo headphone amplifier. Featuring a stereo 6.35mm jack input & 4 stereo 6.35mm headphone jack outputs, the AMIS HA4 offers separate volume controls per channel & a simple layout for ease of operation. The AMIS HA4 is powered by a supplied 12VDC power supply.

Juiced Up (PPA2) Dual Phantom Power Supply is an in-line power supply that provides phantom power for 2 condenser mics. Selectable between 12VDC & 48VDC, it will power nearly any commercially available microphone. The AMIS PPA2 can run off 29 volt batteries or be powered by the supplied 12 VDC power supply.

Get Up 2 Way Stereo Converter converts consumer level signals to professional level. Input will convert a pair of professional balanced XLR signals to a consumer level stereo RCA signal. The stereo path has its own volume control. The AMIS SC2 is powered by a supplied 12 VDC power supply

Get Down 2 Way Stereo Converter converts professional level to consumer level signals.

Let's Split (MCS1) Microphone Splitter / Combiner produces 2 balanced XLR signals, (1 direct, 1 transformer isolated) from a single balanced XLR input. The AMIS MCS1 provides a ground lift switch to eliminate hum.

Let's Split (LSC1) Line Splitter / Combiner produces 2 balanced XLR signals, (1 direct, 1 transformer isolated) from a single balanced XLR line level input. The AMIS LSC1 provides a ground lift switch to eliminate hum.

Mixed Up (PM4) 4 Channel Passive Mixer is a 4 input, 1 output passive mixer that can be used for mixing 4 mics, instruments, or line sources or for converting stereo feeds to mono. The AMIS PM4 requires no batteries or other external power source. The unit features unbalanced 6.35mm jack inputs & outputs and can be used as a 1 in 4 out signal splitter when all channel volumes are run at maximum.



CONTRACTOR TOOLS



Pre Me (PRE1) Mini Microphone Preamp features balanced XLR & unbalanced 6.35mm jack inputs & outputs, switchable 36 volt phantom power, gain control & signal clip LED. Powered by a supplied 12VDC power supply,

Injector (DI1) Passive Direct Injection Box features a balanced XLR output, a 6.35 mm TRS through output, 3 stage pad offering up to 40dB of attenuation & a ground lift switch for hum elimination.

Buzz Off (HE2) Dual Hum Eliminator tool for eliminating hum & signal noise caused by ground loops. The AMIS HE2 has two discreet signal paths via balanced XLR inputs & outputs. The AMIS HE2 is a passive device & can also be used as a converter of balanced & unbalanced signals. As part of the AMIS Contractor Tools range, the AMIS HE2 is an inexpensive

Drop Me 70 volt to line level converter with phoenix to XLR and level control.

AMIS26 2 x 6 Mic/Line Distribution Amplifier. 24VDC Phantom Power switchable per input. Either input can be routed to any of the 6 outputs via front panel dip switches



MP8 8 Channel Monitor Panel. 100/70V Line or Low Impedance Applications. Includes 2.5 inch speaker with volume control. Simply select any of 8 amplifier via the front panel switch and you can monitor its output through the speaker and via an LED array. Signal Present LED provided for each zone for easy troubleshooting. Loop in, loop out terminal strips for inputs from amplifiers and outputs to speakers.

