

## 30 Watt 2RU MIXER-AMPLIFIER



- 3 balanced XLR mic/dual RCA line inputs
- 30 watt output power
- 2 Rack units in height
- 70 volt or 4 ohm operation
- Master treble and bass control
- Channel 1 has priority over channels 2 & 3 (defeatable)
- Facility to add a tone generator module
- Tape output (pre master)
- Balanced line output

The Australian Monitor Installation Series AMC line of amplifiers takes the heritage & reliability of our famous AMIS series & integrates these features into a low cost amplifier format for applications where reliability is everything, but the more elaborate features of our AMIS series are not required. The 30 watt version of the AMC series is a 2 RU mixer amplifier featuring 70 volt line (100v 230/240V version) & 4 ohm outputs & 3 universal mic/line inputs.

Master volume & overall treble/bass controls are provided, along with Voice triggered muting (defeatable) giving channel 1 priority over inputs 2 & 3. There is also facility to internally add a tone generator card.

The Australian Monitor AMC series give the contractor a low cost alternative in applications that are cost sensitive, but still require a high quality of sound reproduction & reliability.

### SPECIFICATIONS

<b>Power output:</b>	30W
<b>Outputs:</b>	4 Ohms, 70/100V
<b>THD before clipping</b>	0.5%
<b>Inputs</b>	3x (Mic/Aux)
<b>Input connectors</b>	3x (XLR/RCA)
<b>Mic sensitivity</b>	1mV+/-0.2mV
<b>AUX sensitivity</b>	0.5V+/-100mV
<b>S/N ratio</b>	> 75dB
<b>Bandwidth</b>	
<b>On 70V terminals</b>	85Hz-15kHz (-3dB +0dB)
<b>Tone Controls</b>	
<b>Bass @ 100Hz</b>	+/- 12 dB
<b>Treble @ 10kHz</b>	+/- 9 dB
<b>Power source (Switchable)</b>	115V 60 Hz 230-240V 50Hz
<b>Current draw (full power)</b>	.73A
<b>Fuses</b>	1A - AC mains & DC
<b>Line Out</b>	1V
<b>Tape Out</b>	300mV
<b>Mic 1 Automatic</b>	Priority over Mic 2/3
<b>Size</b>	19" W x 3.5" H x 7.5" D
<b>Protections</b>	1) Short circuit 2) No Thermal
<b>Output Regulation</b>	96%
<b>Net Weight</b>	13.2lb
<b>Shipping Dimensions</b>	20.1" W x 5.7" H x 11.7" D
<b>Shipping Weight</b>	16.5lb
<b>Warranty</b>	1 year



## ABOUT

Australian Monitor Corporate Headquarters is located in Sydney, Australia. The organization has more than 20 years experience in the design and manufacture of audio amplifiers and associated products. They are a dynamic corporation, priding themselves on excellent customer service, better features and lower priced products for Sound Contractors and Audio Visual Integrators worldwide.

### 70 Voltage cable run distances-to-cable type

50m	AWG26
50m-200m	AWG20
Over 200m	AWG18

### 4 Ohm cable run distances-to-cable type

10m	AWG18
10m-30m	AWG13
Over 30m	Not recommended

