



AMAV AV25PS, AV40PS

Powered speaker systems



At a glance

The AMAV powered Speakers feature

- Supplied as pairs (1 active & 1 passive speaker)
- Powered Stereo speakers
- 25 watt RMS or 40 watt RMS
- Magnetically shielded
- Complete with "U" brackets
- Available in black or white
- Stereo RCA inputs
- Bass, Treble & Volume controls
- Stylish design
- High quality sound reproduction



A more thorough examination

The AMAV AV25PS & AV40PS are active two way stereo speaker systems. Supplied in pairs the AV25/40PS consist of one powered & one passive speaker both are of a compact & architecturally pleasing design & feature on board stereo amplifier, Treble, bass & volume control, power switch, stereo RCA line input, speaker output & installation brackets. The AV25PS features a 5" bass driver & dome tweeter & delivers 25 watts while the AV40PS features a 6.5" bass driver & dome tweeter & delivers 40 watts. The new AMAV AV powered speakers deliver high quality sound reinforcement for a variety of Audio Visual applications. Compact & well designed they are easy to operate & will become a standard in many AV installations.



AMAV AV25PS, AV40PS



AV40PS

AV25PS



AV40PS

AV25 PS

Architectural & Engineering Specification

The speakers shall be of compact, 2 way design with each pair comprising a powered speaker with on board stereo amplifier & a passive speaker. Onboard controls will be available for volume, bass & treble adjustment & mounting will be via "U" style brackets. The speaker will be powered via mains IEC type connector. RMS power rating will be 25 watts/40 watts RMS. The Speaker shall be the AMAV AV25/40PS.

MODEL AV25PS		AV25PS-passive speaker	AV25PS-active speaker
Woofer	Diameter	5"	5"
	Impedance	8Ω	8Ω
Tweeter	Diameter	1" dome	1" dome
	Impedance	8Ω	8Ω
System Specifications	Power	35watts(R.M.S)	35watts(R.M.S)
	Impedance	8Ω	8Ω
	Sensitivity	89dB	89dB
	Frequency response	60Hz to 20k Hz	60Hz to 20k Hz
Power Amplifier	Power output	/	25 watts
	Equalization	/	2 bands EQ ±15 dB
	Frequency response	/	20Hz to 20k Hz
	AC Power input	/	230-240VAC
Dimension (H×W×D)		240mm× 178mm×145mm	240mm× 178mm×145mm
Net weight (one pair)		/	4.8Kgs
Carton		/	430mm×395mm×580mm

MODEL AV40PS		AV40PS-passive speaker	AV40PS-active speaker
Woofer	Diameter	6.5"	6.5"
	Impedance	8Ω	8Ω
Tweeter	Diameter	1" dome	1" dome
	Impedance	8Ω	8Ω
System Specifications	Power	50watts(R.M.S)	50watts(R.M.S)
	Impedance	8Ω	8Ω
	Sensitivity	89dB	89dB
	Frequency response	55Hz to 20k Hz	55Hz to 20k Hz
Power Amplifier	Power output	/	40 watts
	Equalization	/	2 bands EQ ±15 dB
	Frequency response	/	20Hz to 20k Hz
	AC Power input	/	230-240VAC
Dimension (H×W×D)		285mm× 205mm×180mm	285mm× 205mm×180mm
Net weight (one pair)		/	7.6Kgs
Carton		/	500mm×450mm×355mm