

# **Specifications**

	XR6	XR8	XR10	XR12	XR15
Drivers	6.5"W/25mmT	8" W/34mmD	10" W/ 34mm D	12" W/ 44mmD	15"W/44mmD
Freq., Response (-3dB)	80Hz-18kHz	65Hz-18KHz	55Hz-18kHz	50Hz-18kHz	40Hz-18kHz
Freq., Response (-10dB)	65Hz-20kHz	60Hz-20KHz	55Hz-20kHz	40Hz-20kHz	35Hz-20kHz
Sensitvity (db/1M/1W)	91dB	92dB	95dB	97dB	98dB
Impedance	8ohms	8ohms	8ohms	8 ohms	8 ohms
RMS Power	80W	100W	250w	300w	300w
Max SPL (dB/1M)	110dB	111dB	119dB	120dB	121dB
Dispersion (HxV)	90x60	90x60	90x60	100x55	100x55
Harmonic Distortion	<1%	<1%	<1%	<1%	<1%
Connectors	1 x NL4	1 x NL4	2 x NL4	2 x NL4	2 x NL4
Dimensions (WxDxH)mm	225x211x325	277X257X400	321X321X464	415x382x620	485x460x700
Packing Dimensions	480x255x380	595X310X460	375X355X535	465x435x680	545x515x800
Net Weight (kg/pcs)	5.6	6.5	10	18	26
Gross Weight (kg/pr)	13.2	15	12	20	28









Audio Telex Communications Pty Ltd ABN 78 001 345 482

149 Beaconsfield Street, Silverwater, Sydney NSW 2128, Australia

NSW Tel (02) 9647 1411 Fax (02) 9648 3698 VIC Tel (03) 9890 7477 Fax (03) 9890 7977 QLD Tel (07) 3852 1312 Fax (07) 3252 1237 SA Tel (08) 8352 4444 Fax (08) 8352 4488 WA Tel (08) 9228 4222 Fax (08) 9228 4233 NZ Tel (09) 415 9426 Fax (09) 415 9864 International Enquiries: international@audiotelex.com.au • Website: www.australianmonitor.com.au



# XR Speaker Series









#### XR Series Speaker System

The AM Pro XR series speaker systems are a versatile, high performance range of two way injection molded enclosures. Featuring many innovative features such as rotatable high end drivers & fold back kits as standard across most of the range, the XR series are perfect for installations & live sound reinforcement. Whether it be Front of House or fold back applications, foreground music or background fill installations the XR series, which range from a 6" & 34" compression driver all the way through to a 15" & 2" compression driver, have the right speaker for the application. The rotatable High end driver on the XR8, XR10, XR12 & XR15 make them ideally suited for fold back use or for mounting horizontally where low ceiling heights, or impeded sight lines are an issue in installations.

The AM Pro XR series of speaker enclosures represent a significant advancement in injection molded box design & offer a level of audio quality previously only found in speakers many times their price.





#### XR6

- Two way 6.5" woofer & 1" driver
- Highly durable Poly Propylene injection molded cabinet
- Heavy duty protective grill
- High frequency driver protection
- Supplied in pairs with "U" brackets
- Available in black or white

#### XR8

- Two way 8" woofer & 1.5" driver
- Highly durable Poly Propylene injection molded cabinet
- Heavy duty protective grill
- High frequency driver protection
- Supplied in pairs with "U" brackets
- Available in black or white
- Rotatable 90 x 60 (H v V) dispersion horn for horizontal or vertical mounting







#### **XR10**

- Two way 10" woofer & 1.5" driver
- Highly durable Poly Propylene injection molded cabinet
- Heavy duty protective grill
- High frequency driver protection
- Pole mount or eye bolt installation points
- Rotatable 90 x 60 (H v V) dispersion horn for horizontal or vertical mounting

### **XR12**

- Two way 12" woofer & 2" driver
- Highly durable Poly Propylene injection molded cabinet
- Heavy duty protective grill
- High frequency driver protection
- Pole mount or eye bolt installation points
- Rotatable 100 x 55 (H v V) dispersion horn for horizontal or vertical mounting





## **XR15**

- Two way 15" woofer & 2" driver
- Highly durable Poly Propylene injection molded cabinet
- Heavy duty protective grill
- High frequency driver protection
- Pole mount or eye bolt installation points
- Rotatable 100 x 55 (H v V) dispersion horn for horizontal or vertical mounting