



Australian Monitor
INSTALLATION SERIES

Quick Fit

Ceiling Speakers

Description

Easy to install, easy on the eye and easy to listen to, the Australian Monitor Installation Series (AMIS) range of Quick Fit Ceiling Speakers have been meticulously designed to ensure they satisfy both the end client and the installer. The sleek look and sensational sound provide the end client with total satisfaction, whilst the Quick Fit installation mechanism and sonic purity ensures the contractor/installer is fully satisfied.

Quick Fit 8 Ceiling Speaker

The AMIS Quick Fit 8 is a sensational sounding dual cone speaker. Our goal was to achieve the sound of a 'co-axial' but without the weight restrictions that a co-axial speaker normally brings due to its heavy magnet. Being a lighter weight, the AMIS Quick Fit 8 is suitable for almost any ceiling and avoids any bowing of the ceiling which is a regular issue with co-axial ceiling speakers. The AMIS Quick Fit 8 features a 100V line transformer with 15, 10, 5, 2.5 and 1.25 watt taps.

Quick Fit 6 Ceiling Speaker

To ensure seamless continuity throughout your project, we also offer a six inch, quick mounting ceiling speaker, the AMIS Quick Fit 6. The choice of a six and eight inch speaker allows you to utilise the best speaker for the application, yet still maintain the same look throughout the venue. Once again, we have achieved a superb response from a very sleek, compact ceiling speaker. The AMIS Quick Fit 6 also offers a 100V transformer with 10, 5, 2.5 and 1.25 watt tapings.

Quick Fit 5 Ceiling Speaker

The Quick Fit 5 is a sensational sounding 5 inch speaker and metal grill combination. The Quick Fit 5 really stands apart from other four and five inch ceiling speakers on the market, with a warm sound from a discreet and tasteful speaker/grill combination. The Quick Fit 5 offers a 100V line transformer with tapings of 5, 2.5, 1 and 0.33 watts.



Australian Monitor
INSTALLATION SERIES



Specifications - QF8

Driver	8" dual cone full range
Power Rating	15W
Selectable Power Tappings	15W, 10W, 5W, 2.5W, 1.25W
Frequency Response	70Hz - 20kHz
Sensitivity	92dB
Dispersion	100°
Ceiling cutout (mm)	237mm

Specifications - QF6

Driver	6.5" dual cone full range
Power Rating	10W
Selectable Power Tappings	10W, 5W, 2.5W, 1.25W
Frequency Response	90Hz - 20kHz
Sensitivity (1W/1m)	90dB
Dispersion	100°
Ceiling cutout (mm)	193mm

Specifications- QF 5

Driver	5"
Power Rating	8W
Selectable Power Tappings	5, 2.5, 1, 0.33W
Frequency Response	120Hz - 18kHz
Sensitivity (1W/1m)	90dB
Dispersion	100°
Ceiling cutout (mm)	140mm

QF8 Mounting

