

Specifications MP620p



Native Resolution	XGA (1024 x 768)
Projection System	DLP™ by Texas Instruments
Brightness	2200 ANSI Lumen
Lamp	200W, 3000/4000 hours (Normal/Economic mode)
Contrast Ratio	2000:1
Weight	2.7 kg (6lbs)
Noise Level	<29/25 dB (normal / economic mode)
Resolution Support	640 x 350 to 1280 x 1024
Dimensions	11.45 x 3.70 x 9.21 inches (284 x 94 x 231 mm)
Image Size	31" to 300"
Throw Ratio	55"@2m (55"@6.6 feet)
Throw Distance	Min: 1.30m; Max: 10.91m
Lens	F=2.6 to 2.77, f=20.4 to 23.5 mm
Display Colors	Full 16.7 million color palette
Aspect Ratio	4:3/16:9 screen selectable
Horizontal Frequency	31 ~ 82 kHz
Vertical Scan Rate	48 ~ 85Hz
Projection Position	Front/Rear, Table/Ceiling
Input Terminals	Analog RGB: D-sub 15 pin x 1 Component video: D-sub 15 pin x 1(Shared) S-Video: Mini Din 4 pin x 1 Composite video: RCA x 1 PC audio: Stereo mini jack x 1 L/R audio: Stereo mini jack x 1 (shared)
Output Terminals	Analog RGB: D-sub 15 pin x 1 2 Watt Speaker x 1
Speakers	2 Watt Speaker x 1
Video Compatibility	NTSC/PAL/SECAM
Auto Switching Power Supply	100 to 240 V AC, 50 to 60 Hz
Power Consumption	305W (max)
On-Screen Display Language	English/French/German/Italian/Spanish /Korean/Simplified Chinese/Traditional Chinese/Japanese/Russian/Czech/Portuguese/Thai/Polish/Swedish/Dutch/Turkish (17 languages)
Preset Modes / Application Modes	PC Input : Brightest mode Presentation mode sRGB/Photo mode Gaming mode Video mode

AV Input :

Movie mode
Cinema mode
Gaming mode
Photo mode

Functions Digital keystone
Auto adjustment
Freeze
Blank
Auto Off
Quick Cooling
Security Password
Mute
Auto Source detection
HDTV compatible
Macintosh® Compatible
"Mode" Hot Key
Micro dust filter
High altitude mode

Accessories (included) User's manual
Quick start guide
Manual CD
Remote control
Battery for R/C
Soft Carry case
VGA cable
USB cable
PWR cord