

# Model : PD4600

## 46" Plasma Display



### > PD4600 Specifications >

PDP	Aspect Ratio	16:9
	Screen size ( H x V )	1007 x 567.4mm
	Resolution	852 x 480
	Cell Pitch ( H x V )	1.182 x 1.182mm
	Displayable Colors	16.77 million Colors
	Peak Bright	700 cd/m2
	Contrast Ratio	800:1
	Color Temperature	Over 8000 oK
	View angle	Over 160o
	Color(R, G, B)	16.7M(256 x 256 x 256)
	Cell Type	RGB Stripe(BM)
	Video	PC/DTV Signal
Signal	Video System	PAL/SECAM/NTSC
	Video Signal (Component)	480p, 525i, 625i, 720p, 1080i
Control	Function Key	POWER, INPUT, MENU, UP/DOWN, LEFT/RIGHT
	Specially Function	Zoom, Freeze, PIP(with PC mode), Wide, WOW(surrounding sound)
	OSD Language	English / Chinese (simplified) / Chinese (Traditional)
I/O Ports	PC Input	D-SUB 15pin
	DVI Input	30pins DVI connector
	Audio System	AMP. : 10Wx2 (Lever Terminal)
	Add-on Speaker Box	10W +10W (Optional)
	RS-232C	D-SUB 9pin
Option Video I/O Board	Component Video In	RCA x 3 (Y, Cb/Pb, Cr/Pr)
	Audio Input 1	RCA x 2 (R and L) for Component Video and PC
	S-Video In	Mini-Din 4pin for S-VHS Video In
	Composite Video In	RCA x 1 for Composite Video in
	Audio Input 2	RCA x 2 (R and L) for Composite Video and S-VHS video
	Composite Video Out	BNC x 1
	Tuner	
Safety Regulation	FCC(B), UL, C-UL, CE, TUV	
Dimenssion (W x H x D)		
Packing Dimension (W x H x D)	1310 x 850 x 330 mm	
Net Weight / Gross Weight	40.0KG (Including stand) / 47.7KG (W/O Stand)	
AC Input	90~110Vac / 216 ~ 264Vac, 50Hz / 60Hz	
Warranty	One year limited warranty on parts, labor	

> LCD DISPLAYS > CRT DISPLAYS > PROJECTORS > MULTIMEDIA DISPLAYS >

#### CTX INTERNATIONAL, INC.

16720 E. Gale Ave.

City of Industry, CA 91745

Website: [www.ctxintl.com](http://www.ctxintl.com)

Tel: 626.709.1000 Fax: 626.855.7481

© 2003 CTX International Inc. All rights reserved. Specifications are subject to change without notice.



vision<sup>s</sup>everything