

# BenQ Digital Projector Specifications

## MP771



### HIGHLIGHTS

- **3000 ANSI Lumens**
- **XGA Native Resolution**
- **BrilliantColor™**
- **UNISHAPE**
- **Short Throw Ratio Lens**
- **Detachable Keypad**
- **Presentation Timer**
- **Panel Key Lock**
- **Wall Color Correction**
- **3D Color Management**
- **Power on/off Ring Tone**
- **Golden Ratio Color Wheel (6 Segments)**
- **"Q?" Hot Key for FAQ**
- **Quick Cooling**
- **Quick Auto Search**
- **11 Sets of Application Mode**
- **Power saving "Auto Off"**
- **Security Password**
- **My Screen(optional)**
- **High Altitude Mode**
- **HDCP Compatible**
- **12V trigger**

Projection System	DLP™ technology by Texas Instruments®	
Panel	XGA DDR DMD™ x 1	
Native Resolution	XGA (1024 x 768)	
Brightness	3000 ANSI lumens	
Contrast Ratio	2000:1 (Full on/Full off)	
Aspect Ratio	4:3 Native, 16:9 Selectable	
Color	Full 16.7 million color palette	
Lens	F=2.42, f=7.5 mm	
Zoom Ratio	Fixed	
Image Size (Diagonal)	67" to 118"	
Throw Ratio	74"@3.3 feet(73"@1m)	
Lamp	280W, 3000/4000 hours (Normal/Economic mode)	
Computer Compatibility	VGA(640 x 350) to SXGA(1280 x 1024)	
HDTV Compatibility	480i, 480p, 576p, 720p, 1080i	
Video Compatibility	NTSC, PAL, SECAM	
Horizontal Frequency	31-82 kHz	
Vertical Scan Rate	48-85 Hz	
Input Terminals	PC	Analog RGB: D-sub 15 pin x 1 DVI-I(HDCP support)
	A/V	Component Video: D-sub 15 pin (Shared with Analog RGB connector)
		S-Video: Mini Din 4 pin x 1
		Composite Video: RCA x 1
Audio	Stereo mini jack x 1	
Output Terminal	PC	12V Trigger D-sub (15 pin) X 1
	Audio	2 Watt Speaker x 1
Control Terminal	Serial Connector : RS232 8 pin MINI DIN	
	USB Connector : USB x 1, Type mini B	
Dimensions(W x H x D)	10.8 x 5.1 x 13.3 inch (275 x 131 x 338 mm)	
Weight	8.1 lbs (3.7 kg)	
Power Supply	100 to 240 VAC, 50 to 60 Hz	
Power Consumption	Max 365W	
Audible Noise	34/29 dB (Normal/Economic mode)	
On-Screen Display Languages	English/ French/ German/ Italian/ Spanish/ Russian/ Traditional Chinese/ Simplified Chinese/ Japanese/ Korean/ Swedish/ Dutch/ Turkish/ Czech/ Portuguese / Thai/ Polish	
	Application Modes	<b>PC Input:</b>
Dynamic Mode		Dynamic Mode
Presentation Mode		Standard Mode
sRGB Mode		Cinema Mode
Cinema Mode		User 1 Mode
User 1 Mode		User 2 Mode
User 2 Mode		
Functions	3D Color Management	Short Throw Ratio Lens
	Quick Auto Search	Wall Color Correction
	Time Controller	Blank (ECO mode)
	Presentation Timer	Quick Cooling
	Power On/Off Ring Tone	Auto Off
	Panel Key Lock	Security Password
	Resolution Reminder	My Screen(optional)
	11 sets of Picture Mode	HDCP compatible
	"Q?" Hot Key for FAQ	HDTV compatible
	Detachable Keypad	12V trigger
	Freeze	High altitude mode
Accessories (Standard)	Quick Start Guide	Rubber Cover
	Manual CD	(for detachable keypad)
	Remote control w/battery	VGA cable
	Batteries for R/C	PWR cord
Accessories (Optional)	Ceiling Mounting Kit	Spare Lamp Kit
	Presentation Plus	Soft carry case