ProAnnounce Paging System Questionnaire Supplement

INSTRUCTIONS
Please provide the information below. Please include as much detail as possible such as amplifier loads per zone, names of paging positions, zone names, pre-recorded message names, schedule of events, etc…

If not already done so, please describe system overall:

Type of system

Paging Only ☐
Paging and one (1) Background Music (BGM) ☐
Paging and Multiple Background Music (BGM) ☐

Options
Alarms / Chimes ☐
Audio Monitor Panel ☐

Power supply

Mains operation
115 V ☐
230 V ☐

Emergency power supply

None ☐

Battery
Smooth switch to battery ☐
Automatic standby ☐
UPS (for telephone interface) ☐

System Stand-by time
System Operational time

Alarms

Number of alarms

Type of alarms
DIN ☐
Slow whoop ☐
Siren ☐
Post ☐
Telephone ☐
Others (please specify)

Activated by
Clock ☐
External contact ☐
Paging station ☐

Routed as
As a general call ☐
Fixed groups (please specify)
Current selection from paging station ☐

Chime signals

Number of chime signals

Type
4-tone chime ☐
3-tone chime ☐
2-tone chime ☐
1-tone chime ☐

Activated by
Clock ☐
External contact ☐
Paging station ☐

Routed as
As general call ☐
Fixed groups (please specify)
Current selection from paging station ☐

Pre-recorded messages

Stored in Paging Manager ☐
Stored in External Unit ☐

Number of messages (max 25)

<u>Activated by</u>
Clock ☐
External contact ☐
Paging station ☐

<u>Routed as</u>
As general call ☐
Fixed groups (please specify)
Current selection from paging ☐
Combination of message and signal ☐

Duration

Message stacking ☐
Max stacked message length (time)
Number of repeats
Time between repeats

Clock

Yes ☐   No ☐

Atomic clock synchronization ☐

Schedule of events:

Auxiliary audio units

Radio ☐
Cassette ☐
CD ☐
DVD ☐
MD ☐
Mixer ☐
Microphone ☐

Speaker lines

      Number of speaker lines (<100)

      Output voltage   100V ☐
                                 70V ☐

      Overall power of speaker lines
      Power distribution of all lines
      (Please specify)

      Use ProAnnounce standard amplifiers ☐
      Use ProAnnounce remote control amplifiers ☐
      Use Electro-Voice amplifiers ☐
      Use Electro-Voice RT (IRIS) series amplifiers ☐
      Use third party amplifiers ☐

      Speaker line measurements ☐

      Amplifier monitoring ☐
      Spare amplifier switching (max 8 spare amps) ☐
            Number of amplifiers per spare (max 10)

Paging stations

      Number of paging stations and functions needed (attach list)
      Pre-chime announcement (please specify)
      Key functions (please specify)

Logical outputs

      Number of logical outputs
      Description of functions (e. g. ext. relay, subsystems)

Logical inputs

      Number of logical inputs
      Description (e. g. priority, signal from main system)

Volume Control

      Priority relays (attach list of lines associated)