

# **Altec Commercial Ceiling Speakers**



# **509 FAMILY Extended LF Ceiling Speakers**

The 509's are 30 watt, full-range 2-way loudspeakers. The "T" versions are available in either 5 or 30 watt. They can also be purchased with a grill. Freq. Resp. = 80-16,000 Hz; Max SPL = 110dB.



# 409 FAMILY **Premium Duplex® Speakers**

The 409's are 32 watt, full-range coaxial loudspeakers. The "T" versions are available from 4 to 32 watts. They can also be purchased with a grill. Freq. Resp. = 85-18,000 Hz; Max SPL = 112dB.



# 309 FAMILY Standard Duplex® **Speakers**

The 309's are 15 watt, full-range coaxial loudspeakers. The "T" versions are available in either 4 or 8 watt. They can also be purchased with a grill. Freq. Resp. = 85-18,000 Hz; Max SPL = 108dB.



### 209 FAMILY **Utility Ceiling Speak**ers

The 209's provide 10 watts of power and are available in 8 ohms or with a transformer and grill. Freq. Resp. = 80-15,000Hz; Max SPL 104dB @ 8 ohms / 101dB w/ transformer.



### 109 FAMILY **Economy Ceiling Speakers**

When budget is the main concern, these speakers are perfect.

The 109's provide 5 watts and are rated at 8 ohms. Also available with a transformer and grill. Freq. Resp. = 80-15,000Hz; Max SPL = 101dB.

### 6.5 - INCH SPEAKERS

# **407 FAMILY Premium Ceiling Speakers**

These high performance full range speakers are the speakers true professionals choose. Available in an 8 ohm or transformer configuration. Choose between two different transformers - 8 or 16 watts. Freq. Resp = 65 - 15,000 Hz; Max SPL = 105 dB.



# 307 FAMILY **Utility Ceiling Speakers**

Available in two versions, these speakers provide full range response: 10 watts /8 ohms or 10 watts / 4 watt transformer. Freq. Resp. = 95-12,000 Hz; Max SPL = 103dB.

### 4 - INCH SPEAKERS



# **405 FAMILY Premium Ceiling Speakers**

Because quality is always a concern, these speakers are not a compromise. Full Range / High Performance in both 8 ohm and 70/100 volt applications. Freq. Resp. = 60 - 15,000 Hz; Max SPL = 102 dB



# 205 FAMILY **Utility Ceiling Speakers**

A great all purpose 4" - available with or without transformer. Freq. Resp. = 90-18,000Hz; Max SPL = 101dB

# Enclosures and Grilles for 8-inch Ceiling Speakers



5184-E Back enclosure. 0.6 cuft round (for existing construction



Back enclosure, 1.5 cu.ft. round (for new construction)



5189-X Back enclosure. 1.0 cu.ft.



Grille assembly. square, white



5284-WM Grille assembly, square, white, with beveled edges



Back enclosure. 1/4 cu.ft. for 5295-W grille



Grille, round, white,

screw mounting

Accessories for 4-inch Ceiling Speakers

5195-X torsion spring mounted 5295-W



5194-XM Back enclosure, 1/4 cu.ft. for 5294-WM grille



5281-W Ceiling grille, round, white

5295-W Grille, round, white, screw mounting

5181-XM Back enclosure.



5182-XM T-Bar support Back enclosure. 1.0 cu.ft. square 2.0 cu.ft. rectangular

