

9725 GIRARD AVENUE SOUTH MINNEAPOLIS, MINNESOTA 55431-2621

## LETTER OF CERTIFICATION

PREPARED FOR:	TEST DATES:	
	Start:	5/8/01
TELEX COMMUNICATIONS, INC.	Completion:	5/10/01
9600 ALDRICH AVENUE SOUTH BLOOMINGTON, MN 55420	ENVIRON TEST NO.:	27255-1
	PURCHASE ORDER NO.:	231266
ATTN: Mr. Bill Gelow	PURCHASE ORDER DATE:	N/A

This document shall not be reproduced except in full, without the written authorization of Environ Laboratories LLC.

ENVIRON LABORATORIES LLC certifies that five (5) Speakers were subjected to a 48hour Humidity Test. The relative humidity was 95%. The temperature was cycled between 27°C and 35°C with ramp times of 2 hours and no soak times.

MANUFACTURER:	TELEX COMMUNICATIONS, INC.				
DEVICE:	Speakers				
MODEL/PART NO.:	301047-001	301046-004	301045-001		
SERIAL NO.:	01150093 and 01150095	01150071	01150009 and 01150010		

The results of this test apply only to the units identified in this Letter of Certification by device identifier and model / part number, or serial number.

Post humidity test visual inspection revealed no evidence of corrosion. The parts were retained at Environ for further tests.

avin myill

allan Thomas

David M. Gillen Vice President Alan G. Thompson President

ENVIRON LABORATORIES LLC CERTIFICATION NO. 27255-1

800-826-3710 • FAX 952-888-6345 • 952-888-7795 www.environlab.com Page 1 of 2

## **INSTRUMENTATION**

All instrumentation is calibrated regularly by instruments directly traceable to the National Institute of Standards and Technology, and in accordance with MIL-STD-45662A, MIL-I-45208A, ANSI/NCSL Z540-1-1994 and ISO/IEC 17025: 1999.

Equipment Number	Description	Manufacturer	Model No	Last Calibration	Due Calibration	Range
200-139	Temperature Chart Recorder	Honeywell	DR4500AT	1/4/01	7/4/01	-110 to +300°F; (-78.9 to +149°C); 0 to 100% RH
200-140	Temperature Controller	Watlow	922	1/5/01	7/5/01	-99.9 to +392.5°F
500-029	Temperature/ Humidity Chamber	Thermotron	F-135-CHV-25-25	N/A	N/A	-100 to +350°F; 20 to 99% RH