

**EV T252 Loudspeakers**  
**EV Dx34A Digital Parameters**

Loudspeaker System		<b>T252</b>		
Notes		Un-hide cells for revision history and specific system notes.		
Programmer: 1st Rev. - Last Rev.		FD: 07/19/96		
Dx34A Program Title		<b>T252</b>		
Dx34A Configuration		2-Way		
Frequency Band		<b>FR</b>	<b>LF</b>	<b>HF</b>
Dx34A Output		<b>1&amp;2/3&amp;4</b>	<b>1/3</b>	<b>2/4</b>
Edit Menu	Input Master Delay (mS)	2.0		
	Input Master PEQ Freq (Hz)	---		
	Input Master PEQ Q (Q)	---		
	Input Master PEQ Gain (dB)	---		
	Low-Cut Freq (Hz)		45.0	
	Low-Cut Slope (dB/Oct)		12	
	Low-Cut Q (Q)		1.5	
	LSF Freq. (Hz)		300	
	LSF Slope (dB/Oct)		12	
	LSF Gain (dB)		+5.0	
	HPF Freq. (Hz)			1200
	HPF Resp. (Type-dB/Oct)			LR24
	PEQ1 Freq. (Hz)		240	3200
	PEQ1 Q (Q)		2.5	1.9
	PEQ1 Gain (dB)		+3.0	-4.0
	PEQ2 Freq. (Hz)			---
	PEQ2 Q (Q)			---
	PEQ2 Gain (dB)			---
	LPF Freq. (Hz)		1200	
	LPF Resp. (Type-dB/Oct)		LR24	
	HSF Freq. (Hz)			7400
	HSF Slope (dB/Oct)			6
	HSF Gain (dB)			+12.0
	Output Align Delay (uS)		299	0
	Polarity (Normal, Invert)		Norm	Norm
	Digital Output Gain (dB)		0	-5.0
Limiter Thresh. (dBU)		+21.0	+21.0	
Limiter Decay (dB/mS)		50	50	
Limiter Hold (mS)		5	5	
Channel 1 Mode (L,R,L+R)				
Channel 4 Mode (L,R,L+R)				
Knob	Output Knobs (dB)		0	0
	Input Knob (dB)		0	
Options	2-Way L-R Mode	Select Link or Independent		
	Delay Units	uSec		
	Limiter Thresh. Reference	dBU (0dBU=.775v)		
	VU Display	No Peak (dB from clip)		