

	<b>ZX1-90</b> Portable Version	<b>ZX1i-90</b> Fixed Install Version	<b>ZX1i-100</b> Fixed Install Version	<b>ZX1i-100t</b> 70v/100v Version
<b>Frequency Response<sup>(1)</sup></b> (-3 dB)	60 Hz - 20 kHz	60 Hz - 20 kHz	60 Hz - 20 kHz	60 Hz - 20 kHz
<b>Frequency Range<sup>(1)</sup></b> (-10 dB)	48 Hz - 20 kHz	48 Hz - 20 kHz	48 Hz - 20 kHz	48 Hz - 20 kHz
<b>Axial Sensitivity<sup>(1)</sup></b>	94 dB (1W/1m)	94 dB (1W/1m)	92 dB (1W/1m)	92 dB (1W/1m)
<b>Maximum Calculated SPL</b>	125 dB	125 dB	121 dB	121 dB
<b>Horizontal Coverage</b>	90° or 50°	90° or 50°	100°	100°
<b>Vertical Coverage</b>	50° or 90°	50° or 90°	100°	100°
<b>System Power Handling</b>	200W Continuous, 400W Program	200W Continuous, 400W Program	200W Continuous, 400W Program	200W Continuous, 400W Program
<b>LF Transducer</b>	EV8L, 8 in (203mm) Driver	EV8L, 8 in (203mm) Driver	EV8L, 8 in (203mm) Driver	EV8L, 8 in (203mm) Driver
<b>HF Transducer</b>	DH2005, 1 in. (25.4mm) Exit Compression Driver	DH2005, 1 in. (25.4mm) Exit Compression Driver	DH2005, 1 in. (25.4mm) Exit Compression Driver	DH2005, 1 in. (25.4mm) Exit Compression Driver
<b>Nominal Impedance</b>	8 Ohms	8 Ohms	8 Ohms	8 Ohms
<b>Pole Mount</b>	Included	N/A	N/A	N/A
<b>Transformer Taps</b>	N/A	N/A	N/A	6.5, 12.5, 25, 50, 100 watts 70/100v
<b>Connectors</b>	Two NL4 Connectors	4-Pin detachable Phoenix style	4-Pin detachable Phoenix style	4-Pin detachable Phoenix style
<b>Overload Protection</b>	Full protection - all modes	Full protection - all modes	Full protection - all modes	Full protection - all modes
<b>Mounting System</b>	Four M8 studs on bottom of speaker	QuickSAM™ Heavy-Duty Strong-Arm Mounting Bracket	QuickSAM™ Heavy-Duty Strong-Arm Mounting Bracket	QuickSAM™ Heavy-Duty Strong-Arm Mounting Bracket
<b>Built-In Monitor Angle</b>	Yes	No	No	No
<b>Available Colors</b>	Black	Black/White	Black/White	Black/White
<b>Included Accessories</b>	None	QuickSAM™ Mount	QuickSAM™ Mount	QuickSAM™ Mount
<b>Dimensions (H x W x D)</b>	17.75" x 11.12" x 10.35" 451mm x 282mm x 263mm	17.75" x 11.12" x 10.35" 451mm x 282mm x 263mm	17.75" x 11.12" x 10.35" 451mm x 282mm x 263mm	17.75" x 11.12" x 10.35" 451mm x 282mm x 263mm
<b>Net Weight</b>	8.4 kg (18.5 lbs)	8.4 kg (18.5 lbs)	8.4 kg (18.5 lbs)	10.4 kg (23.0 lbs)
<b>Shipping Weight</b>	10.2 kg (22.5 lbs)	10.2 kg (22.5 lbs)	10.2 kg (22.5 lbs)	12.3 kg (27.0 lbs)

(1) Half-space measurements

## The Complete ZX1 Family

The ZX1 is part of a complete compact speaker system product line with models for fixed installation distributed systems.



**Americas**  
Telex Communications Inc.  
12000 Portland Ave South,  
Burnsville, MN 55337, USA  
USA — Phone: 1-800-392-3497, Fax: 1-800-955-6831  
Canada — Phone: 1-866-505-5551, Fax: 1-866-336-8467  
Latin America — Phone: 1-952-887-5532, Fax: 1-952-736-4212

**Europe, Africa & Middle-East**  
EVI Audio GmbH.  
Hirschberger Ring 45, D 94315,  
Straubing, Germany  
Phone: +49 9421 706-0, Fax: +49 9421 706-265

**UK: Telex Communications (U.K.), Ltd.,**  
Unit 26 Fiddlebridge Industrial Center,  
Lemsford Road  
Hatfield, Hertfordshire AL10 0DE, UK  
Phone: +44 1707 280 960  
Fax: +44 1707 265 083

**Asia & Pacific Rim**  
Japan: EVI Audio Japan Ltd.  
5-3-8 Funabashi, Setagaya-Ku,  
Tokyo, Japan 156-0055  
Phone: +81 3-5316-5020,  
Fax: +81 3-5316-5031

**Australia: APAC Audio Pty Ltd.**  
James Ruse Business Park  
Unit 2C 6 Boundary Road  
Northmead NSW 2152  
Phone: +61 2 9683 4752  
Fax: +61 29890 5928

**China: EVI Audio Ltd.**  
Room 2210-2215, Tower B, Far East International  
Plaza, No. 317, Xianxia Road,  
Shanghai, China, Post Code: 200051  
Phone: +86 (21) 6235-1677  
Fax: +86 (21) 6235-1676

**Hong Kong: EVI Audio Ltd.**  
Unit 5, 1/F, Topsail Plaza  
11 On Shum Street  
Shek Mun, Shatin  
Hong Kong  
Phone: +852 2351-3628, Fax: +852 2351-3329

**Singapore: Telex Pte. Ltd.**  
3015A Ubi Road 1, 05-10  
Kampong Ubi Industrial Estate, Singapore 408705  
Phone: +65 6746-8760, Fax: +65 6746-1206

# ZX1



Live For Sound  
www.electrovoice.com



IncredibleSound

# It's your music, your voice, your message.

You need a speaker that can reproduce every note, every inspirational word and every nuance of your style. Introducing ZX1. Compact, lightweight, yet high performance, ZX1 is a reflection of the needs of the high-speed,

time-crunched, high-tech lifestyle you lead. Its versatility is matched only by your imagination, and its look is pure beauty. So while your audience may not be fully aware

of why you sound incredible, you'll know it's because you

chose the very best. . .

## ZX1



**ZX1** offers a wide array of mounting options including an integrated pole mount and removable rubber feet that hide M8 mounting studs. Dual NL4 connectors and an ergonomic molded carrying slot make **ZX1** perfect for portable music, AV rental and mobile audio applications.

**ZX1** shines in monitor wedge applications, especially where the reproduction of vocal frequencies is crucial. Its asymmetrical cabinet design means you simply have to put **ZX1** on its side to achieve a 45° monitor angle. And with the ability to rotate its 90° x 50° horn, you can adjust the dispersion pattern to suit your unique application.