



ClearOne® Conference Phone

The ClearOne® Conference Phone from Gentner offers many superior audio features to enhance any business meeting.

The exclusive Express Conference™ button makes conferencing effortless and convenient. Simply push the button to experience the latest in 3-way plus calling. You'll be instantly linked to Gentner's friendly conference call operators who do the rest. Conference calling has never been so easy!

Our exclusive VTM™ technology allows for 360 degree dynamic audio pickup, while the illuminating LEDs track the direction of the speaker's voice, letting them know they're being heard at the distant location.

ClearOne also uses full duplex operation, enabling free-flowing, natural conversations that allow more than one person to speak at the same time.

With ClearOne, even Internet communications software can be enhanced with full duplex audio. Simply connect it to a PC sound card.

Clearly, Gentner provides the superior technology and breakthrough sound performance for timesaving, effective business meetings. It's truly intelligent.



The ClearOne uses full duplex operation which eliminates clipped audio.

Features and Benefits

- VTM technology for 360-degree dynamic audio pickup
- Full duplex audio so you can talk and listen at the same time
- Echo cancellation eliminates clipped speech
- Background noise reduction produces clearer audio
- Visual feedback indicator indicates direction of audio pick-up
- Connect to a PC to bring full duplex audio to your PC
- Easy to install

Applications

- Home Office
- Small Meeting Rooms
- Executive Office

Specifications

Keypad Functionality

Standard touch-tone keypad
Large on/off key
Flash Key
Volume control
Redial for last number dialed
Color-coded mute key for easy identification
Shift key to access additional features
"Any key" answer

Connections

Analog PBX or public switched telephone network interface
RCA Connector for recording devices
3.5 mini stereo jack for PC sound card

Regulatory

FCC Class B
FCC Part 68, 15

Operating Voltage

90V–120V

Power Consumption

15 watts

Power Source

90V–120V
or 220V–240V available

Safety

UL Certification
CUL Certification

Operation

Temperature: 41–158° F/5–40° C
Humidity: 50–80%

Storage

Temperature: 5–70° C
Humidity: 10–90%

Dimensions

9"x10.5"/9 x 26.7 cm oval

Weight

2.0 lb/.9 kg

Color

Executive black

Part Number

910-156-100