





### EXPANSION CAPABILITIES


Unlike competitive products, the MAXAttach conferencing system can fully expand to include up to four conferencing phones, giving you unprecedented audio coverage. Whether you conduct your meetings from a training room (4 phones), a large boardroom (3 phones) or a conference room (2 phones), you can easily create the optimal conferencing system with MAXAttach.



A.



B.



C.

A. Medium Conference Room

B. Large Boardroom

C. Training Room

### MAXIMIZE YOUR CONFERENCING EXPERIENCE

ClearOne, the company that first brought you wireless tabletop conferencing, now brings you another "first" in innovation. Only the ClearOne MAXAttach™ conferencing system provides unprecedented expansion capabilities to ensure complete microphone and loudspeaker coverage. No matter where participants are seated, conversations are natural and effortless.

The two phone units included in the MAXAttach conferencing system enable even distribution of microphones and loudspeakers as well as centralized access to dialing, mute and volume controls. The MAXAttach features advanced audio technology typically found only in high-end installed audio systems, including Gentner® Distributed Echo Cancellation®, noise cancellation and advanced microphone activation processes.

#### Expandable

MAXAttach is ideal for any size conference room and provides complete microphone and loudspeaker coverage and easy access to controls.

#### Superior Audio

The clear, full sound of the MAXAttach facilitates more natural interaction between participants.

#### One-Touch Conferencing

Press a button and access a conferencing-services operator who can connect an unlimited number of participants.

#### Easy to Use

Intuitive, user-friendly controls are simple to operate.



The MAXAttach is ideal for users who need ultimate flexibility to customize their conference meeting experience.


**ClearOne**  
You're Virtually There™

# PRODUCT BRIEF

## PRODUCT FEATURES

- ▶ **Gentner® Distributed Echo Cancellation®:** Improves audio quality by eliminating echo
- ▶ **Noise cancellation:** Removes background noises from fans or HVAC systems making speech audio easier to understand
- ▶ **Full-duplex sound:** Allows participants on both ends of the call to engage in highly interactive, productive conversations
- ▶ **First-mic priority:** Eliminates hollow "tunnel" sound by activating only the microphone closest to the person speaking
- ▶ **Three microphones:** Provide 360° audio pickup to ensure participants are heard clearly at the far-end of the call
- ▶ **Speed dial:** Stores 10 frequently dialed numbers to improve dialing efficiency
- ▶ **Recording output on base unit:** Connects to a recording device to capture both sides of the conversation

## PRODUCT APPLICATIONS



### Connect up to four MAXAttach phones to provide complete coverage

The MAXAttach expands by connecting additional phones, not just expansion microphones. This creates a better distribution of loudspeakers and microphones so all participants can hear and be heard clearly.

It also provides easy access to user controls such as volume and mute.

All connected phones share control. Volume and mute changes on one phone will affect all phones.

## PRODUCT SPECIFICATIONS

### Dimensions (W x D x H)

Phone section: 10.5" x 10.5" x 3"  
(26.7 cm x 26.7 cm x 7.6 cm)  
Base unit: 4.25" x 5.5" x 2.5"  
(10.8 cm x 14 cm x 6.4 cm)

### Weight

Phone section: 2.7 lb (1.2 kg)  
Base unit: .6 lb (0.27 kg)  
Shipping: 10 lb (4.5 kg)

### Power

Base unit:  
Auto-adjusting power module;  
100-240VAC; 50/60Hz

### Telephone Connection

Analog PBX or PSTN line  
RJ-11C, -12dBm nominal

### Keypad

Alphanumeric standard keypad

### Loudspeaker

Volume: 90dBspl A weighted @ 1 ft  
Bandwidth: 200Hz-3.3kHz

### Record Output

Connector: 2.5 mm mono audio jack  
Impedance: <1000 ohms  
Bandwidth: 200Hz-3.3kHz  
Dynamic range: 60dB  
THD <.01%

### Echo Cancellation

Tail time: 60mS x 3

### Noise Cancellation

Dynamic noise cancellation

### Certifications

FCC part 15 Class A  
FCC part 68  
UL Certified

### Environmental

Operating temperature: 32-122° F  
(0-50° C)

Storage temperature: 41-158° F  
(5-70° C)

Operating humidity: 15 to 80%

Storage humidity: 10 to 90%

### Warranty

2 years

### Part Number

910-158-055

### MAXAttach Includes

MAX phone pods (2)  
MAX base unit (1)  
12' Cat. 5 cable (1)  
25' Cat. 5 cable (1)  
Telephone cable  
Documentation CD  
Quick start guide  
Expansion kit instruction sheet