ClearOne.

TECHNICAL NOTE

→ MAX 101

Max EX and Max Wireless Pod Placement

Description

This document provides guidelines and suggestions for proper placement of Max pods.

Introduction

Proper pod placement is important to ensure best performance from the series of conferencing


Max Wireless

The Max Wireless pod can be placed up to 150' from the base unit. This distance can include going through typical interior drywall. However, going through brick or concrete walls will reduce the usable distance.

Ideally, a Max Wireless should be positioned on an open, flat, surface, such as a table. ClearOne Communications does not recommend placing the pods on or under a shelf, or at the side of a room. The Max phones use boundary mics and the mics need an open flat surface to perform best.

The optimum distance from talker to microphone is 3'. The maximum effective distance from talker to microphone is 8'. As the talker moves farther from the Max phone, the far side may notice a hollowness in the voice quality, and a drop in the voice audio level.

Figure 1 shows a suggested placement of the Max Wireless pod.



→ Figure 1



Max EX (Wired)


Ideally, a Max EX should be positioned on an open, flat, surface, such as a table. We do not recommend placing the pods on or under a shelf, or at the side of a room. The Max phones use boundary mics and the mics need an open flat surface to perform best.

The optimum distance from talker to microphone is 3'. The maximum effective distance from talker to microphone is 8'. As the talker moves farther from the Max phone, the far side may notice a slight hollowness in the voice quality.

Max EX pods can be connected serially, up to 4 units. ClearOne Communications recommends one pod for every six feet of conference table.

Figure 2 shows a suggested placement of two Max EX pods.

→ Figure 2



→ CLEARONE LOCATIONS

Headquarters: Salt Lake City, UT USA 1825 Research Way Salt Lake City, UT 84119 Tel: 801-975-7200; 800-945-7730 Fax: 801-977-0087 sales@clearone.com

Champlin, MN USA

Tel: 801-942-3776 sales@clearone.com

Latin America Offices

Tel: 801-974-3621 global@clearone.com Tel: 801-974-3792 global@clearone.com

London, UK

Hong Kong

Tel: 801-303-3441 global@clearone.com Tel: 801-303-3495

Singapore

global@clearone.com

© 2005 ClearOne Communications Inc. All rights reserved. Other product names may be trademarks of their respective owners. Information in this document subject to change without notice. 801-158-001-01 Revision 2.0