

MAXAttach™

Expandable Tabletop Conference Phones

The industry's first fully expandable tabletop conference phones. MAXAttach comes with two complete phone units and provides premium, full-duplex audio in medium sized rooms. It also features the ability to link up to two additional phone units for unrivaled microphone and loudspeaker coverage in larger rooms.

ClearOne.



UNRIVALED AUDIO
QUALITY, FLEXIBILITY
AND AFFORDABILITY

MAXATTACH APPLICATIONS

- Executive Office
- Medium Conference Room
- Large Conference Room
- Training Room
- Separate Rooms

MAXATTACH ADVANTAGES

Superior Audio Performance

- + Distributed Echo Cancellation® effectively eliminates echo
- + Noise cancellation removes background noises from fans or HVAC systems
- + Full-duplex sound enables participants to speak and listen at the same time without cutting in and out
- + Automatic level controls keep participants' audio balanced and consistent
- + First-mic priority eliminates hollow "tunnel" sound by activating only the microphone closest to the person speaking
- + Three microphones in each phone unit provide 360° audio pickup

Expandability

MAXAttach

- + Comes with two phone units and a single base unit for medium conference rooms; also available in 3-phone and 4-phone kits
- + Link up to four complete phones, not just microphones, for expanded coverage with MAX EX Expansion Kits
- + Divide MAXAttach into multiple phone systems for use in separate rooms with MAX EX Expansion Base

MAX EX Expansion Kit

- + Includes phone and connecting cable to expand MAXAttach room coverage (base not included)

MAX EX Expansion Base


- + Used to divide MAXAttach into multiple phone systems for use in separate rooms to provide unrivaled flexibility and affordability

Ease of Use & Control


- + Simply plug base unit into power and phone line, connect the phones, then dial and talk
- + Features user-friendly telephone style controls
- + Speed dial stores 10 frequently dialed numbers
- + Recording output on base unit connects to a recording device to capture both sides of the conversation
- + Linked MAX phones can be operated using the dial pad of any phone – dialing, mute, volume controls, etc.

> ROOM APPLICATIONS


MAXAttach™




MAXAttach + 1 Exp. Kit



MAXAttach + 2 Exp. Kits



MAX EX Expansion Base



MAX EX Expansion Kit

Use with any MAX Phone to expand coverage up to 4 total units.

Enables MAXAttach and MAX EX Expansion Kits to be used in separate rooms. Includes power supply and 25' cable.

> SPECIFICATIONS

Echo Cancellation

Tail time: 60 ms x 3

Noise Cancellation

Dynamic noise cancellation

Telephone Connection

Analog PBX or PSTN line
RJ-11C, -12 dBm nominal

Keypad

Alphanumeric standard keypad

Loudspeaker

Volume: 90dBspl A weighted @ 1 ft
Bandwidth: 200 Hz–3.3 kHz

Record Output

Connector: 2.5 mm mono audio jack
Impedance: < 1000 ohms
Bandwidth: 200 Hz–3.3 kHz
Dynamic range: 60 dB
THD < .01%

Certifications

FCC part 15 Class A
FCC part 68
UL Certified

Power

Base unit:
Auto-adjusting power module;
100-240 VAC; 50/60 Hz

Environmental

Operating temperature: 32–122° F
(0–50° C)
Storage temperature: 41–158° F
(5–70° C)
Operating humidity: 15 to 80%
Storage humidity: 10 to 90%

Dimensions (W x D x H)

Phone unit: 10.5" x 10.5" x 3"
(26.7 cm x 26.7 cm x 7.6 cm)
Base unit: 4.25" x 5.5" x 2.5"
(10.8 cm x 14 cm x 6.4 cm)

Weight

Phone unit: 2.7 lb (1.2 kg)
Base unit: .6 lb (0.27 kg)
Shipping: 10 lb (4.5 kg)

PART NUMBERS

MAXAttach*

- 910-158-055 (North America)
- 910-158-057 (Europe)
- 910-158-058 (United Kingdom)
- 910-158-056 (Japan)
- 910-158-059 (Australia/New Zealand)
- 910-158-060 (South Africa)
- 910-158-061 (South Korea)
- 910-158-062 (China)

* For MaxAttach plus 1, add -01 to part number; for MaxAttach plus 2, add -02 to part number.

Includes:

- MAX phone units (2)
- MAX base unit (1)
- 12' Cat. 5 cable (1)
- 25' Cat. 5 cable (1)
- Telephone cable
- Documentation CD
- Quick start guide

MAX EX Expansion Kit

910-158-050 (All countries)

Includes:

- MAX phone unit (1)
- 12' Cat. 5 cable (1)
- Documentation CD
- Quick start guide

MAX EX Expansion Base

910-158-048 (North America, Brazil, Taiwan)
910-158-049 (All other countries)

Includes:

- MAX base unit (1)
- 25' Cat. 5 cable (1)
- Telephone cable
- Documentation CD
- Quick start guide



> CLEARONE LOCATIONS

Headquarters:
Salt Lake City, UT USA
5225 Wiley Post Way
Salt Lake City, UT 84116
Tel: 801-975-7200;
800-945-7730
Fax: 801-977-0087
sales@clearone.com

Latin America
Tel: 801-974-3621
global@clearone.com

EMEA
Tel: 44 (0) 1189 036 053
global@clearone.com

APAC
Tel: 801-303-3388
global@clearone.com