


## SUGGESTED RETAIL PRICE LIST

Effective January 1, 2005  
(Replaces January 1, 2004)

## ETA® SYSTEMS

A Creative Light & Sound Company

Division of National Biological Corporation  
1532 Enterprise Pkwy • Twinsburg, Ohio 44087 USA  
330-425-3388 • 800-321-6699 • Fax: 330-425-9700  
http://www.etasys.com E-mail eta@etasys.com



### CONTROLLERS, MICROPROCESSOR, MEMORY CONSOLE, IMAGENATION™ SERIES

Non-volatile memory with program lock protection, programmable scenes, programmable chase sequences, speed adjustable electronic chase, audio sync with sensitivity adjustment, adjustable timed crossfade, crossfade from dynamic manual scene preset to any static preprogrammed scene or chase sequence, program and edit blind capacity, master control, fade to blackout, controller powered from dimmer or 12V DC remote power supply, connects to dimmer with standard 3-pin microphone cable. *Certain models:* superimpose one scene over another with pile-on button, MIDI in/out/thru, DMX 512, 5-pin digital control signal.

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS.	SUGGESTED LIST PRICE
MC8C	8-channel, 4-scene console	10	\$ 500
MC12CM	12-channel console, 8-scene, DMX512 compatible (see IPS-002)	12	700
MC1224CM	24-channel console, 152-scene, DMX512 compatible (see IPS-002)	14	1200
IPS-002	12V Power Supply - Required when DMX512 protocol selected on MC controllers	1	34

### DMX512 DIMMER PACKS, FOUR AND EIGHT CHANNEL, DIGITAL DMX AND MULTIPLEX SIGNAL - ETL LISTED

Multiple protocols: DMX512 and Ultraplex™ (multiplex) 0-10V DC. Analog is optional and requires field modification kit. Microprocessor monitored system featuring: 4 or 8 channel models with 1.2KW or 2.4KW of power. Any phase power hook-up: single, any two phases of three-phase power. Simplified channel assignment utilizing decimal switches on front panel. Low voltage protection: reset breaker located on front panel. Channel Test Circuitry located on front panel. 10 built-in chase sequences and 10 speeds. Individual channel field conversion to relay function. Dual Edison plugs or knock-outs with internal terminal block connectors. Individual channel magnetic circuit breakers. Cooler and safer operation.

MD460DMX-24	Four 600W channels, 2400W max, Truss Mount	13	\$ 600
MD412DMX-48	Four 1200W channels, 4800W max, Truss Mount	14	700
MD812DMX	Eight 1200W channels, 9600W max, Rack Mount	42	1800
MD812DMXKO	Same as MD812DMX with terminal block outlets, Rack Mount	42	1800
MD824DMX	Eight 2400W channels, 19,200W max, Rack Mount	48	2000
MD824DMXKO	Same as MD824DMX with terminal block outlets, Rack Mount	48	2000
	Analog field modification kit for DMX512 Dimmers		200

### CABLES, REMOTE CONTROL (Call for pricing on microphone, DMX512 and analog cables)

### ULTRALIGHT™ LIGHTING FIXTURES

Manufactured from a high-temperature resistant, high-impact, nonconductive, engineered space age material that is maintenance free – will not dent, scratch or rust. UL approved or non UL. Perfect for outdoor applications, standard color black.

PF1	Par 20 light fixture for high-output halogen lamps, with medium screw base socket, gel frame, 1-meter cordset and on/off switch	1	\$ 54 ea. non UL
PF2	Light fixture with gel frame and cordset sized to accept screw-in base R40 120W or 300W lamp. Sold 4 to a carton.	1½	90 ea.non UL 196 ea.UL
PF3	Par 46, 56, or 64, 3-in-1 light fixture with gel frame and ceramic cordset sized to accept up to 1000W lamps. Sold 4 to a carton.	3	140 ea.non UL 240 ea. UL

### TRIPOD STANDS

TS12C	All purpose crank-up tripod stand, 11-foot height maximum, 250 lbs. capacity	49	\$ 650
TB12	T Bar adapter to fit TS12C for truss	5	80

# CONDITIONED POWER DISTRIBUTION

## RETAIL PRICE LIST

Effective January 1, 2005  
(Replaces January 1, 2004)

### PD SERIES

## ETA® SYSTEMS

A Creative Light & Sound Company

Division of National Biological Corporation  
1532 Enterprise Pkwy • Twinsburg, Ohio 44087 USA  
330-425-3388 • 800-321-6699 • Fax: 330-425-9700  
http://www.etasys.com E-mail eta@etasys.com

### AC CONDITIONED POWER DISTRIBUTION (15 amp, 1800 watt models)

MODEL NO.	DESCRIPTION		WT. LBS.	SUGG. LIST PRICE
PD8	8 U-grounded protected Edison AC outlets, spike and surge protection, EMI/RFI filtration	UL	7	\$79
PD8L	8 U-grounded protected Edison AC outlets with dual retractable rack illuminators, high/low on/off switch, spike and surge protection, EMI/RFI filtration	UL	7	99
PD9L	9 U-grounded protected AC outlets (1 "always on" front, 8 back) to accommodate up to 7 UL approved voltage converters, dual retractable rack illuminators, high/low on/off switch, spike and surge protection, EMI/RFI filtration		8	160
PD11LV	11 U-grounded protected AC outlets (8 back switched, 2 back & 1 front "always on"), "always on" digital voltmeter, dual retractable rack illuminators, high/low on/off switch, spike and surge protection, EMI/RFI filtration	ETL	9	240
PD11SS Sequential	11 U-grounded protected outlets (8 back, 2 outlets per stage, 2 back and 1 front "always on"), sequential power up/down, single rack space, remote turn on/off option, spike and surge protection, EMI/RFI filtration, ETL listed.	ETL	10	390

### PRO SERIES – SINGLE RACK SPACE (20 amp, 2400 watt models) ETL listed

PD11P	11 U-grounded protected AC outlets (8 back switched, 2 back and 1 front "always on") spike and surge protection, EMI/RFI filtration	ETL	10	\$220
PD11VP	11 U-grounded protected AC outlets (8 back switched, 2 back and 1 front "always on"), "always on" digital voltmeter, spike and surge protection, EMI/RFI filtration	ETL	10	330
PD11LP	11 U-grounded protected AC outlets (8 back switched, 2 back and 1 front "always on"), spike and surge protection, EMI/RFI filtration, dual retractable rack illuminators, high/low on/off switch	ETL	10	250
PD11LVP	11 U-grounded protected AC outlets (8 back switched, 2 back & 1 front "always on"), "always on" digital voltmeter, dual retractable rack illuminators, high/low on/off switch, spike and surge protection, EMI/RFI filtration	ETL	10	380
PD11SSP Sequential	11 U-grounded protected AC outlets (8 back switched, 2 outlets per stage, 2 back and 1 front "always on"), sequential power up/down, spike and surge protection, EMI/RFI filtration	ETL	10	490
PD11LVSP Sequential	11 U-grounded protected AC outlets (8 back switched, 2 outlets per stage, 2 back and 1 front "always on"), "always on" digital voltmeter, dual retractable rack illuminators, high/low on/off switch, sequential power up/down, spike and surge protection, EMI/RFI filtration	ETL	10	650

### SEQUENTIAL, LINKABLE, POWER UP/DOWN FOUR-STAGE SYSTEM and ACCESSORIES

PD11SP Sequential	9 U-grounded protected AC outlets (8 back, 2 outlets per stage, 1 front "always on"), 4 stage sequential power up/down, spike and surge protection, EMI/RFI filtration	ETL	10	\$490
PD420VS Sequential	14 U-grounded protected outlets (2 or 4 per circuit), four 20 amp circuits, total 9600 watts, 80 amps, single or three phase power up, each phase circuit breaker protected, "always on" digital voltmeter readout accessing all circuits, external .125 amp fuse protected transformer, two-unit rack space	ETL	21	1100
PS220 NEW	2 U-grounded protected AC outlets, 20 total amps, spike and surge protection, self-contained low voltage power supply, L.E.D. indicators for power, sequencing and channel status, 3-wire remote interface and linkable communications port. Form: 3-gang box.	CS	3	375
KL3R	3-wire input key lock contact closure interface for remote turn on/off application. LED on/off status indicator, key removal in on or off position. 2 keys standard. Form: 1-gang box, painted black.		1	78
KL3RR	1 unit rack-mounted version of above		3	99

### AC LINE VOLTAGE REGULATORS (20 amp input, 15 amp regulated output)

PD10VRS Sequential	10 U-grounded AC protected outlets (8 regulated, 2 always on), 4 separate power up/down sequential circuits, L.E.D. monitored with field adjustable rate		25	\$990
--------------------	--	--	----	-------

### HIGH WATTAGE AUDIO POWER DISTRIBUTION — ETL listed

PD66	6 circuits (two 30 amp terminal blocks with knock out access and four 20 amp circuits with one or two duplex receptacle per circuit), 140 amps, double rack space	ETL	20	\$800
PD620	6 20-amp circuits with one or two duplex receptacles per circuit, double rack space	ETL	20	750

CE Compliant models available with IEC 320 connectors

Prices and specifications are subject to change without notice.

# CONDITIONED POWER DISTRIBUTION

## RETAIL PRICE LIST

Effective January 1, 2005  
(Replaces January 1, 2004)

### ISOBAR / ISOTEL TECHNOLOGY SERIES

### POWER PROTECTION SERIES

## ETA® SYSTEMS

**A Creative Light & Sound Company**

Division of National Biological Corporation  
1532 Enterprise Pkwy • Twinsburg, Ohio 44087 USA  
330-425-3388 • 800-321-6699 • Fax: 330-425-9700  
<http://www.etasys.com> E-mail [eta@etasys.com](mailto:eta@etasys.com)

### FREE-STANDING / WALL-MOUNTED MODELS — UL/CUL 1449 Listed, 15 amp capacity

MODEL NO.	DESCRIPTION	WT. LBS.	SUGG. LIST PRICE
PD4IB	4 AC outlets, 6' cord, 2 isolated filter banks, spike/surge, EMI/RFI protection, 3 diagnostic LEDs, \$ 50,000 insurance protection	3	\$ 125
PD6IB	6 AC outlets, 6' cord, 3 isolated filter banks, spike/surge, EMI/RFI protection, 3 diagnostic LEDs, \$ 50,000 insurance protection	4	\$ 140
PD6IT	6 AC outlets, 6' cord, 3 isolated filter banks, spike/surge, EMI/RFI protection, 2 lines (RJ11) modem/fax connectors, 3 diagnostic LEDs, \$ 50,000 insurance protection	4	\$ 160
PD6IBAV	6 AC outlets, 6' cord, 3 isolated filter banks, spike/surge, EMI/RFI protection, 3 diagnostic LEDs, 2 lines (RJ11) modem/fax connectors, 2 sets (F) coaxial connectors, \$ 50,000 insurance protection	4	\$ 160
PD6IBHG	6 Hospital-grade outlets, 12' cord, 3 isolated filter banks, spike/surge, EMI/RFI protection, 3 diagnostic LEDs	4	\$ 160
PD8IB	8 AC outlets, 12' cord, 4 isolated filter banks, spike/surge, EMI/RFI protection, 3 diagnostic LEDs, \$ 50,000 insurance protection	4	\$ 160
PD6ISHG	6 Hospital-grade AC outlets, 6' cord, 120 volt, 1800 watt capacity Isolation Transformer	59	\$ 795

### RACK-MOUNTED MODELS — UL Recognized

PD12	12 (6 front, 6 rear) AC outlets, 15 amp, 12' Cord, 2 isolated filter banks, spike/surge protection, \$ 25,000 insurance protection	6	\$ 99
PD12IB	12 (2 front, 10 rear) AC outlets, 15 amp, 12' Cord, 2 isolated filter banks, spike/surge, EMI/RFI protection, 3 diagnostic LEDs, \$25,000 insurance protection,	6	\$ 199
PD12IBP	8 (10 front 20-amp, 2 rear 15-amp) AC outlets, 20-Amp 12' Cord, 1 isolated filter bank, spike/surge, EMI/RFI protection, 3 diagnostic LEDs, \$ 25,000 insurance protection	7	\$ 259

### POWER PROTECTION SERIES — UL/CUL Free-Standing or Rack-Mounted

PD7BC	7 AC outlets, 15-amp capacity, 10' cord, balanced circuit, 2 filter banks, spike/surge, EMI/RFI protection, protected satellite/CATV/telephone jacks	5	\$ 249
PD1MK	Accessory 1-space rack mounting bracket kit, for Models PD7BC and PD8BC	1	\$ 15
PD11VBC	11 AC outlets, (1 front, 10 rear) 15-amp capacity, 10' detachable cord, voltmeter, balanced circuits, 3 filter banks, spike/surge, EMI/RFI protection, protected satellite/CATV/telephone jacks	17	\$ 599
PD11VABP	11 AC outlets, (1 front, 10 rear) 15-amp capacity, 10' detachable cord, voltmeter, ampmeter, balanced or isolated power modes, spike/surge, EMI/RFI protection, protected satellite/CATV/telephone jacks	26	\$ 1599
PD2MK	Accessory 2-space rack mounting bracket kit, for Models PD11VBC and PD11VABP	1	\$ 15

Prices and specifications are subject to change without notice.

## LIGHTRUSS™ TRUSS SYSTEMS – 8" AND 14" TRIANGULAR

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS.	SUGGESTED LIST PRICE
A-242	24" aluminum Truss (2 feet)	4	\$ 100
A-243	36" aluminum Truss (3 feet)	8	120
A-244	48" aluminum Truss (4 feet)	10	140
A-222	60" aluminum Truss (5 feet)	12	150
A-246	72" aluminum Truss (6 feet)	13	180
A-247	84" aluminum Truss (7 feet)	16	190
A-248	96" aluminum Truss (8 feet)	17	220
A-249	108" aluminum Truss (9 feet)	18	240
A-223	120" aluminum Truss (10 feet)	20	250

### TRUSS ADAPTERS, STEEL 8" AND 14" TRIANGULAR

A-233	Triangular flat adapter	5	\$ 140
A-236	Beveled base plate	18	250

### RADIUS CORNER AND TEE ADAPTERS, ALUMINUM 8" AND 14" TRIANGULAR

A-1201	4-way tee-up right-hand	10	\$ 410
A-1202	4-way tee-up left-hand	10	410
A-1203	4-way tee-down right-hand	10	410
A-1204	4-way tee-down left-hand	10	410
A-1205	Apex-up cross	10	410
A-1206	Apex-out cross (may also be used apex-in)	10	410
A-1207	Apex-up 135° corner	6	250
A-1208	Apex-out 135° corner	6	250
A-1209	Apex-in 135° corner	6	250
A-224	Apex-up 90° corner	6	250
A-225	Apex-out 90° corner	6	250
A-226	Apex-in 90° corner	6	250
A-227	Apex-up 3-way tee	6	250
A-228	Apex-out 3-way tee	6	250
A-229	Apex-in 3-way tee	6	250
A-237	Apex-in corner tee (available only in 14" truss)	6	290
A-239	Apex-out corner tee (available only in 14" truss)	6	290

### "I" TRUSS, 8" AND 14"

A-211	60" aluminum Truss (5 feet)	10	\$ 120
A-212	120" aluminum Truss (10 feet)	15	200

### LIGHTRUSS™ 8" AND 12" BOX

A-1401	24" aluminum Truss (2 feet)	5	\$ 180
A-1402	36" aluminum Truss (3 feet)	8	180
A-1403	48" aluminum Truss (4 feet)	11	220
A-1404	60" aluminum Truss (5 feet)	14	220
A-1405	72" aluminum Truss (6 feet)	17	312
A-1406	84" aluminum Truss (7 feet)	20	312
A-1407	96" aluminum Truss (8 feet)	20	350
A-1408	120" aluminum Truss (10 feet)	20	400

### CORNERS, TEES & ADAPTERS, ALUMINUM 8" AND 12" BOX

A-1441	90° corner	8	\$ 390
A-1442	90° corner tee	10	550
A-1443	3-way tee	10	550
A-1444	4-way cross	12	770
A-1445	4-way branch tee	12	770
A-1446	5-way cross tee	14	990
A-1447	6-way branch tee	16	1200
A-1433	Flat adapter	6	150
A-1440	Beveled base plate	19	250

PAINTING	MOST COLORS AVAILABLE AT 50% SURCHARGE. CALL FOR AVAILABILITY.		
----------	--	--	--