

Executive Videoconferencing Room System

With unparalleled simplicity for the end user, Emblaze-VCON's new room system – xPoint™ – enables executives, managers and educators with dispersed colleagues and operations to collaborate more clearly and effectively across continents. By delivering a life-like visual experience over IP and ISDN networks, Emblaze-VCON's user experience relies on superior video and audio and real-time manageability. In a world of video, xPoint™ brings users face-to-face with the people and organizations they need to be in touch with daily, allowing them to turn any videoconference into a fully interactive workgroup meeting with only a click of a button.

True Collaboration Solution

In addition to providing value as an advanced videoconferencing solution, the xPoint™ incorporates advanced data conferencing capabilities, allowing users to share or receive presentations and various multimedia formats such as audio clips, video multimedia, still images and more. Sharing data is easy, either by connecting a USB flash disk with your presentation or connecting your laptop to the integrated VGA input.

In addition to the camera input, a VCR/DVD can be connected to an additional input allowing movies or training videos to be played to the remote side, with full audio, and the ability to hear the conference presenter along with the movie sound.

The dual monitor capability allows simultaneous view of the local and remote parties, in full size, on separate displays. When data sharing is in progress, the remote party and the data shared can be displayed in full screen on separate screens.

Conducting a multi party broadcast session is available using the Emblaze-VCON Interactive Multicast™ technology. From tens to hundreds of participants per call, chairing a broadcast call enables controlling the presenting party passing the floor between participants, and locking the call when all required parties are connected.

Advantages of Conferencing With xPoint™

- Provides TV-like video quality using advanced video standards.
- Various network types: IP (up to 4MB) and ISDN (up to 512Kbps)
- H.264 video support up to 4 Mbps
- Advanced data sharing capabilities with multiple user options
- Native 16:9 wide screen display support
- Dual monitor support
- CD-quality audio using 20 KHz ultra-wide band audio
- Web-based management for easier control and administration
- Optional Accessories
Tabletop pod
3 Speaker System
- Supports encrypted conferences using the H.235 encryption standard

**Make a Call**

Type a Number / Name Call type Bandwidth

Call**Back****xPoint**
Video Made Easy**HD**
SERIES

Specifications

Emblaze-VCON Ltd. Headquarters

Beit Rakefet
1 Emblaze Square
POB 2220
Ra'anana 43662
Israel
Tel: +972-9-7627800
Fax: +972-9-7627801

Emblaze-VCON, Inc., Americas

2 University Plaza, Suite 201
Hackensack, NJ 07601
USA
Tel: +1-201-883-1220
Fax: +1-201-883-1229

Emblaze-VCON China Representative Office

Unit 1321, Tower B. COFCO Plaza
8 Jianguomennei Avenue
Beijing, 10005
China
Tel: +86-10-6526-9791
Fax: +86-10-6526-9790

Emblaze-VCON GmbH Germany

Schmellerstr. 23
D-80337 Munchen
Germany
Tel: +49-89-76757142
Fax: +49-89-76757143

Emblaze-VCON Italy Via Portuense 1555

Commercity M27
00050 Ponte Galeria (Rome)
Italy
Tel: +39-06-400-43110
Fax: +39-06-400-43113

Emblaze-VCON UK

London House, 42 Brook St.
London, W1K 5DB
United Kingdom
Tel: +44 (0)117 302 6795
Fax: +44 (0)117 302 6794

Video Specifications

Transmission Speed
H.323: 64 Kbps - 4Mbps
ISDN 64 Kbps -512 Kbps (4xBRI)

Video Standards

H.261, H.263, H.263+/++
H.264

Live Video Resolution

QCIF (176 x 144 pixels)
QVGA (320 x 240 pixels)
CIF (352 x 288 pixels)
SIF (352 x 240 pixels)
VGA (640 x 480 pixels)
4CIF (704 x 576)
4SIF (704 x 480)
720p (1280 x 720 pixels) incoming
only

Video Frame Rate

Up to 10 fps: 64 Kbps
Up to 20 fps: 96 to 192 Kbps
Up to 30 fps: 256 Kbps and higher

Video Inputs

1 Composite and S-Video

Video Outputs

1 each: S-video, Composite, Digital
Video Interface (DVI), VGA

HD Simulcast™

Chair or Participant in any
Interactive
Multicast session
Integrated Broadcast Viewer
Uses bandwidth-efficient IP
multicast

Audio Specifications

Audio Features

Full duplex echo cancellation
Automatic noise suppression (ANS)
Automatic gain control (AGC)

Audio Standards

20 KHz: AAC-LD
7 KHz: G.722, G.722.1
3.4 KHz: G.711, G.723.1,
G.728, G.729
AMR (3G)

Data Specifications

Data Sharing Methods
Laptop plug in (via Tabletop Pod)
USB storage key
Documents: PPT, PPS
Video clips (AVI, MPEG, WMV, etc.)
Audio clips (WAV, MP3)
Graphic files (BMP, GIF, TIF, etc.)

HD DualStream™

Sharing of file, or the VGA input
H.239 support
Tandberg DuoVideo support
Sending and receiving capability
1 live video source + 1 data source
Resolutions supported:
XGA, SVGA, VGA, CIF, QVGA, QCIF,
4CIF

Networking Specifications

Standards Supported

ITU-T: H.323 v4.2
Annex Q (FECC)
ISDN: H.320, H.221, H.242, H.230

H.323 QoS Features

DiffServ
IP Precedence
Firewall port sync
NAT IP address mask
Port pinholing
Adaptive Bandwidth Adjustment
Packet loss recovery (FEC)
Packet ordering
Packet duplication control
Jitter correction
Lip sync correction
Overhead prediction
Max packet size adjustment

Peripheral Specifications

Pan-Tilt-Zoom Camera Unit

Picture - 1/4-color CCD
Focal length - 3.1mm to 31mm
Pan-Tilt range - +/-100o Pan, +/-25o
Tilt
Zoom range - 10x (optical), 40x
(digital)
Horizontal resolution
460 TVL (PAL), 470 TVL (NTSC)

Monitors Configurations

Single DVI, VGA or TV
Dual: DVI + VGA
Dual: VGA + TV
Dual: DVI+TV

Features Specifications

Dialing Modes

Manual
Speed dial
Personal address book
Online directory
Multicast chair
Broadcast viewer

Security

Encryption using H.235 (AES)
Using Emblaze-VCON
SecureConnect
DES, 3DES and AES support
AES is NIST validated
Supports Emblaze-VCON
Frontier
— Firewall traversal
— Network address translation
Supports restricted access to
users via admin

Control

International remote control
Embedded web-based
management

Directory Services

1000+ local number directory
10,000+ global number
directory
H.350 support (MXM mode)
LDAP online directory support
- OpenLDAP
- Microsoft ILS, SiteServer,
Active
Directory and Exchange
- Sun iPlanet
- Netscape Directory
Search and filter queries

Environmental

0 - 40°C temperature
15 - 80% humidity
Universal power supply
Operating voltage: 120V or
230V
Operating frequency: 50 Hz or
60 Hz

Language Support

English, French, German,
Italian, Spanish (Spain and
Latin), Portuguese (Brazil),
Chinese and Japanese

EMBLAZE VCON

Video Made Easy

www.emblaze-vcon.com

Emblaze-VCON Ltd

1 Emblaze Square
P.O.B 2220
Ra'anana 43662
customercare@emblaze-vcon.com

EMBLAZE VCON

