

**Specifications****Digital-6 Plus**

Dimensions:	2.55" / 6.48cm W x 3.9" / 9.9 cm H x 1.1" / 2.8 cm D
Weight:	4.32 oz . / 122.4 g (dry)
Frequency Range:	100-10,000 Hz
Output Level:	140 mW into 32 Ohms at 10 percent thd
Signal-to-Noise Ratio:	>55 dB at 1 mV
Distortion:	<2 percent
Transmission Type:	FM, medium bandwidth (60 KHz)
RF Frequency Range:	37 Channels, 72-76 MHz
Sensitivity:	3.5 uV typical, 7uV max for 20 dB S/N
Controls:	On-Off /Volume, Preset Selector, Channel Selector (hidden)
Earphone Jack:	Standard 3.5 mm Mono
Power Requirements:	2xAA batteries
Battery Life:	40 hours with Alkaline types

**Notice**

Gentner Communications Corporation assumes no liability for improper use or operation of this equipment. The user is cautioned to operate the volume controls at the lowest acceptable level, and in a manner that will not cause damage to hearing. Ear pieces and accessories should be worn using good judgment and for their intended purpose. To avoid entanglement, the ear pieces and neck loops should be removed and stored promptly after use and before sleeping.

Users are cautioned that changes or modifications not expressly approved by Gentner Communications Corporation could void the user's authority to operate the equipment.

If you experience problems with this equipment, contact Gentner Communications Corporation