



## IDCam™ Flexible Gooseneck Camera

The IDCam™ video camera from ClearOne, formerly VideoLabs, is a full-motion, color camera that is used in photo identification applications. The IDCam connects easily to a Windows®-based or Macintosh computer through a USB adapter or a video capture card. The IDCam is then used to provide high-quality image captures to ID card creation software.

### The Ultimate Photo ID Tool.

The IDCam's flexible gooseneck design with swivel camera head makes it easy to precisely position the camera for proper head and shoulder framing from a distance of four to eight feet. The IDCam also features a 1/4" CCD image sensor with 16 mm C-mount lens for excellent, high-quality image captures every time. And the IDCam is perfectly sized to sit on a desktop, workstation, or cart.

Using the two-button brightness control on the base of the camera, you can adjust the IDCam to any lighting environment without the need for an



The IDCam provides high quality image capture for photo ID applications.

external flash. This functionality makes it possible to integrate the IDCam into any ID badging system.

The IDCam provides S-video or composite video feeds for connection to USB adapters, video capture cards, monitors, and other video display devices. With its built-in microphone and preamplifier, the IDCam can also be used to display or record presentations and demonstrations.

The IDCam is a multi-function camera that provides all the features and flexibility needed for photo identification applications:

- Compatible with most Windows and Macintosh photo ID software packages
- 1/4"/6.35 mm color CCD image sensor with 16 mm C-mount lens ensure high-quality images
- Flexible gooseneck design makes it easy to position the camera for accurate image capture
- S-video or composite output for connection to USB adapter, video capture cards, monitors, or televisions
- Line-level audio provided through an integrated microphone and preamplifier



### IDCam at Work.

The IDCam is the perfect size to conveniently place on a desktop or work station. It is used primarily to take photos for student IDs, corporate security cards, membership cards, or guest passes. However, the integrated microphone and preamplifier give the IDCam full presentation and recording capabilities as well.

## Specifications

### Dimensions (DxWxH)

7" x 7.5" x 22"  
18 cm x 19 cm x 56 cm  
Gooseneck: 20"/50.8 cm

### Weight

4.2 lb/1.9 kg

### Operating Temperature

14 to 122°F/-10 to 50°C

### Storage Temperature

-4°F to 140°F/-20°C to 60°C

### Power Supply

12VDC

### Current Consumption

300mA

### Image Sensor

1/4"/6.35 mm CCD

### Total Pixels

NTSC: 542 (H) x 492 (V)  
PAL: 542 (H) x 582 (V)

### Number of Effective Pixels

NTSC: 512 (H) x 492 (V)  
PAL: 512 (H) x 582 (V)

### Number of Scanned Lines

NTSC: 525 lines  
PAL: 625 lines

### Frames per Second (FPS)

NTSC: 30fps  
PAL: 25fps

### Resolution

Horizontal: Min. 330TVL (center area) NTSC & PAL  
Vertical: Min. 350TVL (center area) NTSC, min. 400TVL PAL

### Signal to Noise Ratio

46dB, Condition: AGC off, weight on

### Minimum Illumination

3 lux

### Lens

16 mm C-mount

### Focus Range

11"/.28 m to 50'/15.24 m

### Iris

Electronic

### Gain Control

Auto

### Sync. System

Internal only

### Audio

Integrated condenser microphone with preamplifier for line-level output

### Connectors

1 S-video output  
1 Line-level (audio) output  
1 Power input

### Video Formats

NTSC or PAL

### Camera Controls

Adjustable brightness control  
Flickerless mode

### Included Accessories

25'/7.6 m and 6'/1.8 m S-video/audio cables  
S-video to Composite Adapter  
12VDC power supply

### Exterior Color

Black