



# Educational Cameras

# TeachCam® Video Presentation Camera

The powerful TeachCam® from ClearOne is a full-motion, color camera, that produces sharp video images with excellent color reproduction. Using either an S-video or composite video connection, you can easily present your video images on a variety of video display devices such as TVs, plasma screens, and projectors, or record your video on a VCR. Connection to a computer requires a video capture card or a USB adapter.

# The Ultimate Teaching Tool

In addition to outstanding video images and clear audio, the TeachCam features a built-in light source at the base of the camera—the IllumaBase®. The IllumaBase gives the TeachCam the functionality of a 35 mm slide projector and a microscope, making it an invaluable resource for science classes, art history classes and more. When the IllumaBase is used with the included IllumaBoxes and IllumaSlides, the TeachCam can display 35 mm slides, specimen boxes and microscope slides. The TeachCam also includes a microscope adapter kit

#### TeachCam at Work

Using the TeachCam allows you to turn your class-room into a cooperative and interactive learning environment. From student experiments to instructor demonstrations, the TeachCam provides an easy way to share and record projects for enhanced learning. The TeachCam is also ideal for transmitting images and video to remote locations via videoconferencing. An excellent choice for educators, the TeachCam is easy to use and extremely reliable.



The TeachCam teaching tool is ideal for classroom presentations and demonstrations.

with 26 mm, 28 mm and 34 mm couplers for easy connection to most industry standard microscopes.

The TeachCam's 27" flexible gooseneck with swivel camera head is ideal for users of all ages, making it easy to position the camera for accurate image capture and display. And the camera's six-button keypad provides simple control of image settings.

With its built-in microphone and amplifier, the TeachCam is well equipped to capture and transmit audio for recorded demonstrations or presentations. This audio capability also makes the TeachCam a great choice for videoconferencing.

The TeachCam incorporates all the features and flexibility you need in a classroom setting:

- Built-in IllumaBase LED lighting base for viewing and presenting slides, specimen boxes, and microscope slides without using projectors or microscopes
- Flickerless mode to eliminate flicker and color hunting when the TeachCam is used with fluorescent lighting and microscopes
- Compatible with most monitors, TVs, VCRs, video capture cards, LCD and DLP projectors
- Nordic box carrying case with complete accessory package

#### **Specifications**

#### **Dimensions**

7" x 7.5" x 29"

(18 cm x 19 cm x 73 cm) Gooseneck: 27" (65 cm)

### Weight

4.3 lb (1.95 kg)

#### **Operating Temperature**

14° – 122° F (-10° – 50° C)

# **Storage Temperature**

 $-4^{\circ} - 140^{\circ} \text{ F } (-20^{\circ} - 60^{\circ} \text{ C})$ 

# **Power Supply**

12 VDC

#### **Current Consumption**

300mA

#### **Image Sensor**

1/4" (6.35 mm) CCD

#### **Total Pixels**

410 K

#### Number of Effective Pixels

NTSC: 768 (H) x 492 (V) PAL: 752 (H) x 512 (V)

# **Number of Scanned Lines**

NTSC: 525 lines PAL: 625 lines

#### Frames per Second (FPS)

NTSC: 30fps PAL: 25fps

#### Resolution

Horizontal

NTSC, PAL: Min. 480 TVL (center area)

Vertical

NTSC, PAL: Min. 480 TVL (center area)

#### Signal to Noise Ratio

46dB, Condition: AGC off, weight on

### Minimum Illumination

1.5 lux at F2.0

#### Lens

8 mm C-mount

#### Focus Range

 $\frac{1}{4}$ " - 50' (.6 cm - 15.24 m)

# Iris

Electronic

#### White Balance

Auto

#### **Gain Control**

Auto

# Sync. System

Internal only

## Audio

Integrated condenser microphone with preamplifier for line-level output

#### Connectors

- 1 S-video output
- 1 Line-level (audio) output
- 1 Power input

#### Video Formats

NTSC or PAL

#### Camera Controls

Adjustable gain control

Automatic or manual white balance Positive or negative color inversion Color or black and white selection

# Flickerless mode

Included Accessories
Nordic box carrying case

28 mm and 34 mm microscope

couplers

Custom eyepiece adapter

 $Five\ IIIumaSlides$ 

Two IllumaBoxes

Camera positioning bracket

25'/7.6 m and 6'/1.8 m S-video/audio

cables

S-video to Composite Adapter

BNC adapter

12VDC power supply

### **Exterior Color**

Black

#### Part Number

910-171-150

ClearOne Communications, Inc. ~ 1825 Research Way, Salt Lake City, UT 84119 ~ 1-800-945-7730 ~ www.clearone.com