## 106

## 1:2 Microphone Line & Distribution Amplifier







The Kramer 106 is a high quality line & distribution amplifier for balanced mono microphone signals. It takes one dynamic or condenser microphone input and distributes the signal to two line level outputs.

- Mic Input Selector Condenser or Dynamic.
- Phantom Power 48V DC.
- **S/N Ratio** 81dB.
- Level (Gain) Controls Individual (-14 to +68 db) and master (+ 37 to + 68dB) output adjustments.
- Compact Size Part of the Kramer TOOLS™ family of compact, high quality and cost effective solutions.

## **TECHNICAL SPECIFICATIONS**

INPUT: 1 microphone mono balanced on 3 pin terminal block

connector.

OUTPUTS: 2 mono balanced line outputs

on 3 pin terminal block

connectors.

MAX. OUTPUT LEVEL: 27Vpp (22dBm). BANDWIDTH: > 40kHz.

81dB. S/N RATIO:

CONTROLS:

Mic. Type selector pushbutton, - 14dB to + 68dB LINE OUT trimmers (MASTER trimmer at max), + 37dB to + 68dB master (LINE OUT trimmer

at max).

Input:  $\dot{A}C$ , output: DC. COUPLING:

AUDIO THD +NOISE: 0.18%. AUDIO 2nd HARMONIC: 0.16%.

12 VDC, 132mA DC. POWER SOURCE: DIMENSIONS: 12 cm x 7.5 cm x 2.5 cm (4.7" x 2.95" x 0.98",

W, D, H).

WEIGHT: O.3kg (O.66lbs) approx. ACCESSORIES: Power supply (12V, 500mA),

mounting bracket.