VA-15xl **6 Channel Balanced Audio Mixer**






The VA-15xI is a 6 channel mixer for mono balanced audio signals on XLR connectors. It inputs 6 channels of any combination of line or microphone level audio signals to a balanced mixed audio and a headphone signal output.

FEATURES

- **S/N Ratio** 76dB (unweighted) and 72dB (microphone).
- Inputs 6 line or microphone level (individually selectable).
- Phantom Power 48V DC on each input (individually selectable).
- Level (Gain) Control 6 for each input, master and headphone.
- Desktop Size Compact size. Can be rack mounted in a 1U rack space with the optional RK-MEDN adapter.

TECHNICAL SPECIFICATIONS



INPUTS:	6 audio, with selectable line $(10k\Omega)$ or Mic ($4k\Omega$ with phantom voltage), balanced, on female XLR
OUTPUTS:	connectors. 1 audio, 50Ω balanced on a male XLR connector. One headphone output, 250mW max into 8Ω.
MAX. OUTPUT LEVEL: BANDWIDTH (- 3dB):	Mix out: 26Vpp, Phones out: 4Vpp. 20kHz.
S/N RATIO:	76dB unweighted (line), 72dB (Mic).
PHANTOM VOLTAGE: CROSSTALK: CONTROLS:	+ 48V typ. - 64 dB@20kHz, all hostile. Line (each): - 54 to + 6dB; Mic (each): - 54 to + 52dB; Master: - 79 to + 6dB (line level inputs); Phones: - 77 to +11dB.
COUPLING: AUDIO THD + NOISE:	AC (inputs), DC (mixed output). 0.021%.
AUDIO 2nd HARMONIC:	0.002%.
POWER SOURCE:	12VDC; 500mA.
DIMENSIONS:	24.5cm x 18cm x 4.4cm
	(9.6" x 7" x 1.7", W, D, H).
WEIGHT:	1.4kg. (3.1lbs.) approx.
ACCESSORIES:	Power cord, TP to balanced audio adapter.
OPTIONS:	RK-MEDN Rack adapter holds one unit in two vertical spaces.



KRAMER ELECTRONICS. Ltd