


| | The I Provide the second se | COLUMN TO AND ADDRESS OF | AND DESCRIPTION OF A DE |
|---------------|---|--------------------------|--|
| 12V DC | OUTPUT 1 | OUT | PUT 2 |
| DigiTOC | | | KRAMER |
| 1:2 DVI F | Reclocking Distrib | outor | VM-2DVI-R |
| | | INPUT | LIVE ON |
| CANCES STREET | A DAY OF A D | 1 Sauna | |

The **VM-2DVI-R** is a distribution amplifier for DVI-D video signals. It reclocks and equalizes the signal and distributes to two identical outputs. Use Kramer DVI cables for best results.

FEATURES

- Max Data Rate 1.65Gbits/sec.
- Input/Output DVI-D signal on a DVI-I Molex 29pin female connector.
- Compact Size Part of the Kramer DigiTOOLS[™] family of compact, high quality and cost effective digital solutions.



TECHNICAL SPECIFICATIONS

INPUT: OUTPUTS: MAX DATA RATE: POWER SOURCE: DIMENSIONS: WEIGHT:

ACCESSORIES: OPTIONS: 1 DVI, 1.2Vpp; DDC signal 5Vpp (TTL). 2 DVI, 1.2Vpp; DDC signal 5Vpp (TTL). 1.65Gbits/sec. 12VDC, 400mA. 12 x 7.5 x 2.5cm (4.7" x 2.95" x 0.98"), W, D, H. 0.3kg. (0.66lbs.) approx. Power supply, mounting bracket. 19" rack adapters RK-T1, RK-T3.

KRAMER ELECTRONICS, Ltd

