VP-200xI

1:2 Computer Graphics Video Line & Distribution Amplifier



Compatible with HDTV component video signals when used with a breakout cable such as the Kramer C-GM/3RVF.






The VP-200xI is a high performance line and distribution amplifier for computer graphics video signals with resolutions ranging from VGA through UXGA and higher. It provides controls to compensate for signal losses inherent in long cable runs.

FEATURES

- High Bandwidth 405MHz (- 3dB).
- HDTV Compatible.
- Level (Gain) and EQ (Peaking) Controls.
- Compact Size Part of the Kramer TOOLS™ family of compact, high quality and cost effective solutions.



TECHNICAL SPECIFICATIONS

INPLIT:

Analog red, green, blue signals - 0.7Vpp/75 Ω , H & V sync, TTL level, on an HD15F connector.

2 analog red, green, blue signals - 0.7Vpp/75 $\!\Omega,\,H$ & V syncs-TTL level, on OUTPUTS:

HD15 connectors.

VIDEO BANDWIDTH (- 3dB): 405MHz. DIFF. GAIN: 0.08%. DIFF. PHASE: 0.05 Deg. K-FACTOR: < 0.05%. S/N RATIO: 73dB

Level: - 0.4 to + 3.5dB, EQ.: 0 to + 8dB @ 100MHz. CONTROL:

COLIPLING: AC

POWER SOURCE: 12VDC, 60mA. 12cm x 7.5cm x 2.5cm DIMENSIONS: (4.7" x 2.95" x 0.98", W, D, H.).

0.25kg. (0.55lbs.) approx. WEIGHT: Power supply, mounting bracket. ACCESSORIES:

OPTIONS: VA-50P power supply with six 12VDC outlets.

RK-T1, RK-T3 rack adapters.

