So much more than excellent sound



C^M**7**

A unique medium throw speaker with very high SPL in an ultra compact design with constant coverage.

Featuring 18 flying points - four of which are fully adjustable - and a customized u-bracket included as standard with every speaker, the C-Range is an extremely versatile installation speaker series.

The distinct new C^M7 in the C-Range speaker series from MACH powerfully projects every nuance of pure sound in any environment you choose.

Simple to fly

With a unique flexibility in mounting, the innovative CM7 allows complete versatility when setting aim points in the application




















CM7

- Unique medium throw speaker with very high SPL in an ultra compact design with constant coverage
- A 2-way speaker designed as a compact top box with a controlled dispersion pattern
- One 8" mid-woofer with a very low power compression and high power handling
- The tweeter is a 1" compression driver with a constant coverage horn
- Designed specifically for applications in which high SPL and clarity are required
- Ideal for small to medium sized venues in combination with a subwoofer or as a delay speaker

SPECIFICATIONS

Power rating IEC268:	300 watt
Power rating peak:	1200 watt
Sensitivity 1w/1m:	96dB(avg)
Max SPL, calculated long term:	121dB
Max SPL, peak:	127 dB
Frequency range +/-3dB:	80 Hz - 20 kHz
Dispersion angle avg:	H 90 x V 60 deg
Nominal impedance:	8 ohm
Recommended amplifier:	400 watt in 8 ohm

WEIGHT, MEASUREMENTS AND PHYSICAL SPECIFICATIONS:

40 x 34,9 x 33,8 cm (15.7 x 13.7 x 13.3 inches)	
15kg (33 pounds)	
Finish: Black Safe Coat coating with other RAL colors optional	
2 mm steel with foam backing	
2 x Speakon® NL 4 and barrier strip terminals	
Included U-bracket	
Eyebolt part no. 93940002	
Multi Spider bracket part no. 93943040	
Cluster bracket X 2 part no. 93943046	
.Cluster bracket X 3 part no. 93943047	

WHAT IS THE C-RANGE?

- Powerful output in a compact design
- Innovative adjustable "spider bracket system" for multiple horizontal and vertical flying options
- Fast and easy mounting with 18 flying points for complete versatility
- Flexible, easy connection in seconds with recessed speakon and barrier strip terminals
- Natural sound reproduction
- Customized u-bracket included as standard
- Trapezoidal cabinet design allows for flexible and discrete fixing
- Safe coat scratchproof surface and extruded aluminum profiles give an exceptionally strong and robust cabinet
- Fast and easy access to all serviceable parts














360° of excellence. At every angle the C-Range brings you ergonomics in design and functionality.







The speaker comes black as standard with any RAL code color choice as optional.







The innovative C-Range spider bracket system allows multiple positioning with ease.

