

# So much more than excellent sound



## Ci4, Ci6, Ci8

The Ci products are a unique series of In-Fill speakers providing a brilliant hi-fi performance with clear speech intelligibility in an attractive design.

The distinct new Ci 4, Ci 6 and Ci 8 are acoustically optimized for pleasant clarity and openness.

The cabinets have been shaped with an attractive design and the simplest installation in mind. Featuring a special mounting system that dramatically cuts installation time while providing the ultimate flexibility; the Ci series comes with everything included in the box.

Ideal for applications in commercial venues such as cafés, clubs, department stores, conference rooms and hotels that require high fidelity In-Fill sound.

### Easy handling

The C' 4, 6 and 8 are extremely simple to install and adjust.



  
**Mach**  
[www.mach.dk](http://www.mach.dk)

The Ci 4, 6 and 8 are extremely straightforward to install with minimum of tools required for mounting and adjusting. All necessary brackets and auxiliary brackets are included as standard.

The Ci series have been designed as two way speakers with a conical horn delivering uniform dispersion allowing further flexibility to positioning.

## Ci4, Ci6, Ci8

- MACH TF (tool free) mounting bracket with unique, 6 vertical and 6 horizontal positions.
- Auxiliary mounting bracket that can flexibly adapt to any imaginable solution, including extremely tight surface mounts.
- Natural clear sound
- Weather resistant housing and transducers
- Quick release system for mounting speaker on bracket without tools
- Easily attached Safety Wire between speaker and bracket.
- Push button terminals
- The complete MACH solution included in every box: 2 Speakers, 2 MACH TF brackets, 2 Auxiliary brackets, 2 Safety wires, 8 Screws, 8 Wall plugs and 1 Manual



360° of excellence. At every angle the C-Range brings you ergonomics in design and functionality.

SPECIFICATIONS:	CI 4	CI 6	CI 8
Power rating IEC 268:	50W	65W	125W
Power rating peak:	200W	260W	500W
Sensitivity 1w/1m:	87dB	89dB	93dB
Max SPL, peak:	110dB	113dB	120dB
Max SPL, calculated long term:	104dB	107dB	114dB
Frequency response +/- 3 Db:	120Hz – 20Hz	90Hz – 20Hz	70Hz – 20Hz
Configuration:	4" woofer + 3/4" soft dome tweeter	6" woofer + 3/4" soft dome tweeter	8" woofer + 1" soft dome tweeter
Dispersion angle:	90x90 degree conical	90x90 degree conical	90x90 degree conical
Nominal impedance:	8 ohm	8 ohm	8 ohm
Recommended Amplifier:	70W	100W	175W
<b>WEIGHT, MEASUREMENTS AND PHYSICAL SPECIFICATIONS:</b>			
Dimensions (HxWxD):	207x150x120 mm 8,15x5,91x4,72 in	275x200x160 mm 10,83x7,83x6,30 in	395x290x220 mm 15,55x11,42x8,66 in
Net weight:	2,5 kg (5 lbs)	4 kg (9 lbs)	6 kg (13 lbs)
Finish:	Molded cabinet	Molded cabinet	Molded cabinet
Grille:	1 mm aluminum with foam backing	1 mm aluminum with foam backing	1 mm aluminum with foam backing
Input Connectors:	Push terminals	Push terminals	Push terminals
Rigging hardware included:	MACH TF bracket Aux Mounting bracket	MACH TF bracket Aux Mounting bracket	MACH TF bracket Aux Mounting bracket

**Mach**

A Martin Professional Product

Mach Speakers A/S • Perspektivvej 2 • 9900 Frederikshavn • Denmark • Tel. +45 98 43 35 66 • Fax +45 98 43 14 15 • www.mach.dk