

SPECIFICATIONS - T-REX

PHYSICAL

- Size (L x W x H)..... 490 x 164 x 190 mm (19.3 x 6.5 x 7.5 in)
- Weight 7.5 kg (16.5 lbs)

CONSTRUCTION

- Housing aluminum and steel
- Finish electrostatic powder coating

THERMAL

- Maximum ambient temperature (T_a) 40° C (104° F)
- Maximum surface temperature 60° C (140° F)

INSTALLATION

- Minimum distance to combustible materials 0.3 m (12 in)
- Minimum distance to illuminated surfaces 1.0 m (39 in)
- Minimum clearance around fan and air vents 0.1 m (4 in)

CONTROL

- Control method sound-activated

ELECTRICAL, EU MODEL

- Input 3-prong IEC male socket
- AC Power 230 V, 50 Hz
- Primary fuse 2.5 AT / 250 V, P/N 05020010
- Maximum power and current 270 W, 1.2 A @ 230 V, 50 Hz

ELECTRICAL, UK MODEL

- Input 3-prong IEC male socket
- AC Power 245 V, 50 Hz
- Primary fuse 2.5 AT / 250 V, P/N 05020010
- Maximum power and current 270 W, 1.1 A @ 245 V, 50 Hz

ELECTRICAL, US MODEL

- Input 3-prong IEC male socket
- AC power 125 V, 60 Hz

- Primary fuse 5.0 AT / 250 V, P/N 05020018
- Maximum power and current 270 W, 2.4 A @ 110 V, 60 Hz
- Maximum power and current 270 W, 2.2 A @ 120 V, 60 Hz

ACCESSORIES

- Martin DMX Switch Pack, 210-245 V 90758200
- Martin DMX Switch Pack, 100-130 V 90758300
- Osram 24V/250W ELC 50 h halogen lamp 97000104
- Philips 24V/250W ELC 500 h halogen lamp 97000107
- G-clamp 91602003
- Half-coupler clamp 91602005