

OUTLINE



SSC08 MINI SCREENSTAR 0.8X
CONVERSION LENS

SIZE	1-16838	REV
B	SHEET 1 OF 1	A

USED ON:
MATERIAL:

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES AND
INCLUDE CHEMICALLY APPLIED
OR PLATED FINISHES

P/N SUFFIX DEFINITION
-1 CONVERSION COATING
-2 PAINTING
-3 MARKING
-R REWORK

THE CONTENTS OF THIS
DOCUMENT ARE PROPRIETARY
TO NAVITAR, ITS USE IS
AUTHORIZED ONLY FOR
RESPONDING TO REQUEST FOR
QUOTATION OR PERFORMANCE
OF WORK FOR NAVITAR

FINISH:

TOLERANCES AS FOLLOWS
DEC. .XXX ± .005
DEC. .XX ± .010
FRACT. ± 1/64
ANGLES ± 30'
CONCENTRICITY .003 TIR
BREAK ALL SHARP EDGES
.005 MIN. .010 MAX.
MAX. SURF. ROUGHNESS: 32

SCALE: 1:1



DR: DJM

CH: R. E. PODLENA

APP: R. E. PODLENA

DATE DR: 3/23/2005

DO NOT SCALE DRAWING



CHAMFER ALL THREADS 30°
TO ROOT DIAMETER