

OUTLINE

USED ON:

MATERIAL:

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES AND
INCLUDE CHEMICALLY APPLIED
OR PLATED FINISHES

P/N SUFFIX DEFINITION

-1 CONVERSION COATING
-2 PAINTING
-3 MARKING
-R REWORK

THE CONTENTS OF THIS
DOCUMENT ARE PROPRIETARY
TO NAVITAR, ITS USE IS
AUTHORIZED ONLY FOR
RESPONDING TO REQUEST FOR
QUOTATION OR PERFORMANCE
OF WORK FOR NAVITAR

FINISH:

TOLERANCES AS FOLLOWS
DEC. .XXX ± .005
DEC. .XX ± .010
FRACT. ± 1/64
ANGLES ± 30'
CONCENTRICITY .003 TIR
BREAK ALL SHARP EDGES
.005 MIN. .010 MAX.

SCALE: 1:1

DR: DJM


CH: R.E. PODLENA

APP: R.E. PODLENA

DATE DR: 3/16/2005

DO NOT SCALE DRAWING

0.0 inch 1.0
0.0 mm 25.0



CHAMFER ALL THREADS 30°
TO ROOT DIAMETER

NAVITAR
ROCHESTER, NEW YORK

SSC125 MINI SCREENSTAR 1.25X
CONVERSION LENS

SIZE
B

1-16842

SHEET 1 OF 1

REV
A