

WEIGHT = 3.25 LBM

## OUTLINE

**USED ON:**

**MATERIAL:**

UNLESS OTHERWISE SPECIFIED  
DIMENSIONS ARE IN INCHES AND  
INCLUDE CHEMICALLY APPLIED  
OR PLATED FINISHES

**P/N SUFFIX DEFINITION**

- 1 CONVERSION COATING
- 2 PAINTING
- 3 MARKING
- R REWORK

THE CONTENTS OF THIS  
DOCUMENT ARE PROPRIETARY  
TO NAVITAR, ITS USE IS  
AUTHORIZED ONLY FOR  
RESPONDING TO REQUEST FOR  
QUOTATION OR PERFORMANCE  
OF WORK FOR NAVITAR



**FINISH:**

**TOLERANCES AS FOLLOWS**  
DEC. .XXX ± .005  
DEC. .XX ± .010  
FRACT. ± 1/64  
ANGLES ± 30'  
CONCENTRICITY .003 TIR  
BREAK ALL SHARP EDGES  
.005 MIN. .010 MAX.

**SCALE: 1:1**


**DR: R. PODLENA**

**CH:**

**APP:**

**DATE DR: 2/28/2005**

**DO NOT SCALE DRAWING**



**CHAMFER ALL THREADS 30°  
TO ROOT DIAMETER**

**SST300 SCREENSTAR 3X CONVERSION  
LENS**

**SIZE  
B**

**1-16789**

SHEET 1 OF 1

**REV  
A**