



Amazingly compact
Amazingly bright



Philips Multimedia Projectors

Let's make things better.



PHILIPS

features:

XG1



- 1100 ANSI lumens
- XGA resolution

SV1



- 1400 ANSI lumens
- SVGA resolution

cBright series



Compact (4.0"x12.9"x8.9") (HxWxD)



Weight (7,9 lbs; 3.6 kg)



Complete picture control (Digital Freeze, Digital Zoom, Auto Image, Picture formats 4:3 or 16:9)



USB (hot plug&play mouse control and USB audio)



Digital keystone (digital keystone correction)



Ceiling mountable



Philips Air System™ for silent operation

- Unique 1 cable concept for data, USB mouse and USB audio connection
- Easy plug&play
- 200W long-lasting UHP lamp for uniform images, rich colors and brightness over time
- Hot plug&play USB mouse control and USB audio
- Advanced compatibility for most video and PC/Mac data up to SXGA
- Auto-image for trouble-free operation and optimal image quality
- Kensington lock socket
- Switchable audio for video and data

First Choice Warranty:

- 3 years parts and labor, excluding lamp**
- Toll-free technical support
- 1 year, 24-hour roadside assistance



	XG1 LC 4341	SV1 LC 4331
LCD	3x 0.9" high-temperature poly-silicon active matrix LCDs	
Resolution	XGA resolution (1024x768)	SVGA resolution (800x600)
Number of pixels	2,359,296	1,440,000
Brightness	1100 Ansi Lumens	
Contrast	310:1	
Lamp	UHP™-compact 200W (1500 hours), end user replaceable	
Lens	F/2.0-2.2 ; f = 36.5 – 46.6 mm 1.3x Manual Zoom; Manual Focus Projection distance 3.2' - 39.3' (image diagonal 20" - 300")	
Input signals	Video NTSC 3.58, 4.43 / PAL B/G, N, M / SECAM Data PC and MAC compatible, Multi scan VGA-SXGA; Auto Image Horizontal Scan rate: 15-100 kHz; Vertical Refresh rate: 50-120 Hz Bandwidth 140 MHz	
Input connectors	Video 1x S-Video (Y/C DIN), 1x CVBS Audio/Video (3x RCA) Data 1x D-sub (15 pin) Other 1x USB type B connector (upstream) Power in 100 - 240V, 50/60 Hz; 200 W	
Output connectors	Audio 1x Stereo Audio (3.5 mm. stereo jack) Other Monitor out 1x D-sub (15 pin)	
Specialties	Long life and constant light output over entire lamp life projection lamp Auto-image for trouble-free operation and optimal image quality Full PC mouse control via RC unit and USB USB Audio for sound from an external source on the projector 37dB Philips Air System for silent operation Digital keystone correction, digital zoom/freeze, picture format 4:3 or 16:9 Kensington lock socket	
Dimensions	4.0" x 12.9" x 8.9" (102 x 328 x 226mm) (HxWxD)	
Net weight	79 lbs; 3.6 kg	
Operating temperature	41 .. 95 °F (+5 .. +35 °C)	
Package	cBright XG1 Compact remote control Power cord, Combi VGA/USB cable (1.8m) Audio/Video cable (3x RCA, 2m) Lenscap Soft carrying bag CD-ROM User Guide (UK, GE, FR, ES, PT, NL, IT) Quick Set up card (UK, GE, FR, ES, PT, NL, IT)	cBright SV1 Compact remote control Power cord, Combi VGA/USB cable (1.8m) Audio/Video cable (3x RCA, 2m) Lenscap Soft carrying bag CD-ROM User Guide (UK, GE, FR, ES, PT, NL, IT) Quick Set up card (UK, GE, FR, ES, PT, NL, IT)
Optional accessories	UHP™ 200W replacement lamp (LCA3111) Ergonomic trackerball remote control (LCA4117) Ceiling mount (LCA2210/00)	
Model Number	LC4341	LC4331

Information subject to change without notice.

Projection distance	Image diagonal size					
	Tele zoom		Wide zoom			
[inch]	[meters]	[inch]	[meters]	[inch]	[meters]	[meters]
40	1.0	80	2.0	62	1.6	
60	1.5	120	3.0	93	2.4	
70	1.8	141	3.6	109	2.8	
80	2.0	161	4.1	124	3.2	
100	2.5	202	5.1	156	4.0	
150	3.8	303	7.7	234	5.9	
200	5.1	405	10.3	316	8.0	
250	6.4	506	12.9	395	10.0	



More Information

Fax Information System
Technical Support
Sales Information

(865) 521-4341
toll free 888-873-4672 (USA)
1-888-327-3636

www.philipsusa.com

Design and specifications are subject to change without notice.
*Available in the US, Western Europe. Check with your dealer for similar coverage in other regions.
**Warranty is for 3 years or 2500 hours, whichever comes first. Time kept by internal clock.
All trademarks are property of their respective owners.

Let's make things better.



PHILIPS