



Travelling light  
Travelling bright



UGO  
Series

Philips Multi Media Projectors

*Let's make things better.*



**PHILIPS**



Travelling light  
Travelling bright



**features:**



800 ANSI lumens

800 ANSI lumens



XGA resolution

SVGA resolution



2.86 lbs.

2.86 lbs.



Compact design - < 2 dm<sup>3</sup>



Easy plug & play



Digital picture enhancement

- Dimensions; 10.90" x 1.89" x 6.96" (WxHxD) < 2 dm<sup>3</sup>
- Net weight 2.86 lbs; ca 1.3 kg
- Advanced compatibility for both data and video input; compatible with main notebook computers
- High contrast ratio; 800:1 (Full on/off)
- Digital picture enhance technologies; Digital Zoom (x10), Digital Freeze, Digital Keystone correction
- Intuitive Graphic User Interface (GUI) for ease of use
- Auto voltage for safe usage around the world
- Robust, reliable technical design
- Suitable for meeting rooms for 2 to 20 people
- Kensington lock

**First Choice Warranty:**

- 2 years parts and labor, excluding lamp
- Toll-free technical support\*
- 24-hour RoadSide assistance



**technical specifications**

**DMD™** 1x 0.67" DMD™  
X-lite 786,432 pixels, Time sequential (1024x768)  
S-lite 480,000 pixels, Time sequential (800x600)

**Brightness** 800 ANSI lumens

**Contrast** 800:1 (Full on/off)

**Lamp** New 130 W UHP lamp  
End user replaceable  
1000 hours

**Lens** F3.0 ; f= 20.3 mm  
Fixed Focal length; Manual Focus  
Proj. Dist. 1.2 - 6.8m; Diagonal (36 - 200)"

**Digital features**  
*Input signals*  
**Video** NTSC 3.85, 4.43 /PAL -, N, M /Secam in 4:3 and 16:9 formats  
**Data** PC and Mac compatible, Multi scan VGA, SVGA, XGA, SXGA via high advanced scaling technology. Auto image control  
Hor. scan rate: 15 - 91 kHz; Vert. Refresh rate 50 - 85 Hz.  
110 - 120 V / 220 - 240 V (Full range); 50/60 Hz; 180 W

**Power in**  
*Input connections*  
**Video** S-Video (Y/C DIN)/Video (RCA)/ Stereo Audio (2x RCA)/ YCbCr  
**Data** Mini sub-D data (15 pin)/PC Stereo Audio (M3.5 stereo jack)  
Serial mouse (9pin Mini DIN); USB port / PS/2

**Main** Main input socket (3 pin)

**Specialities** 48 mm Ultra Thin Profile  
800 : 1 Contrast Ratio  
Advanced compression technology for full automatic adjust multi scan data input handling, VGA up to SXGA resolutions to full screen  
Intuitive Graphic User Interface (GUI) for ease of use  
Full plug & play compatible (DCC 1 / 2b)  
Full Mirror function  
Acoustical Noise <39 dBA

**Dimensions** 10.90" x 1.89" x 6.96" (WxHxD); <2 dm<sup>3</sup>

**Net weight** 2.86 lbs; ca 1.3 kg

**Package** UGO LC5141/LC5131  
Remote Control + 2x AAA batteries  
Power cord (1.8m) (2 cords, Continental Europe and USA)  
VGA Cable (1m)  
PC Audio cable  
Mouse cable set; 1m, PS/2 ; 1m, USB  
Audio/Video RCA Cable (1m, Video/Audio stereo)  
S-Video cable (1m)  
Soft carrying bag  
User Guide (8 languages - CD-Rom, plus Quick Reference Guide)

**Executions** X-lite LC5141  
S-lite LC5131

**Optional acc.** LCA 3113—130 W replacement UHP lamp

**More information** FAX INFORMATION SYSTEM: (865) 521-4341  
TECHNICAL SUPPORT: toll free 1-888-873-4672 (USA)  
SALES INFORMATION: 1-888-327-3636

Image diagonal size		Projection distance	
[inch]	[meters]	[inch]	[meters]
36	0.94	47	1.2
60	1.52	79	2.0
80	2.03	106	2.7
100	2.54	134	3.4
120	3.05	161	4.1
150	3.81	201	5.1
200	5.08	268	6.8

Values are estimates

[www.philipsusa.com](http://www.philipsusa.com)

Design and specifications are subject to change without notice.  
 Digital Light Processing, DLP, Digital Micromirror Device and DMD are trademarks of Texas Instruments.  
 \* Available in the US, Western Europe. Check with your dealer for similar coverage in other regions.  
 KID Design 2002.85

Let's make things better.



PHILIPS