



Revolabs Solo™ Universal Wireless Adapter for Handheld Microphones

Benefits include:

Natural Mobility

Plug in the Solo XLR Adapter to your handheld microphones for wireless freedom during open mic meetings, Q&A sessions, classrooms, etc. No more duct taping wires to the floor to prevent accidents.

Rechargeable & Long Battery Life

Eight hours of continuous use on a single charge. The quick recharge capability will have you back to nearly a full charge in less than a 1-hour lunch break.

Light and Durable

At only 0.5 ounces, the Solo XLR adapter is virtually unnoticeable on the handheld. Great looking, but tough as nails, designed to withstand drops and abuse.

Interference Free

Revolabs Solo products use digital spread spectrum wireless technology that prevents RF interference from degrading audio quality.

Security

Each Solo XLR Adapter uses state of the art digital encryption (128 bit) for secure connections.

Unmatched Audio Performance

The XLR Adapter provides a robust and secure wireless link to any dynamic handheld microphone. Wideband audio (100-8000hz) provides for exceptional voice reproduction for sound reinforcement and many other applications.

The Solo XLR Adapter is compatible with all Revolabs Solo™ Systems containing **MaxFlex™** technology, allowing up to 16 (24 in EU) devices to operate in the same space. Combinations of Wearables, TableTops and XLR Adapters can be used interchangeably to optimize audio collection for any application.



Applications:

- Financial/Education/Legal/Medical
- Audio augmentation for large rooms
- Conference centers
- Q&A sessions, Panel groups
- Town meetings



63 Great Road, Maynard, MA 01754
1-800-326-1088
www.revolabs.com
info@revolabs.com

solo®
it's with you

Revolabs Solo™ XLR Adapter

Technical Specifications

Charging Requirement

- Solo Executive Charger Base 5V DC, 2 Amps (switching power supply varies by country)
- Solo Desktop Base

Range

Up to 100' (30 meters) approx. (no obstructions)

Microphone Compatibility

Dynamic microphones with XLR type connector (i.e. Shure SM58 or equiv.)

Battery

Lithium Polymer, 8 hours talk time approx.

Charge Time

2 hours approx.

Audio Bandwidth

100-6800 Hz

Encryption

128-bit

Size

- 0.9" (2.4 cm) x 0.8" (1.95 cm) x 3.5" (8.89 cm)

Weight

0.05 lb (0.02 kg)

Shipping Weight

1.0 lbs (5.45 kg)

Environmental Requirements

Temperature
40° to 105° F (5° to 40° C)
operating Humidity
20% to 85%

Warranty

- One year



1. Mute button - press to mute, un-mute and pair microphone
2. Rubber collar - durable and impact/strain protection
3. XLR connector - balanced audio for dynamic microphones
4. LED display - visual status for mute, un-mute, and pairing
5. Audio Out port - 2.5mm, unbalanced
6. Power/Charging Port - docks to all Solo charge stations



63 Great Road, Maynard, MA 01754
1-800-326-1088
www.revolabs.com
info@revolabs.com

