

# SONY®



Ideal for CD production, this basic master recorder is capable of recording analog sources in a 44.1kHz Super Bit Mapping recording, and Set up menu provides more user flexibility and convenience.

**NEW**

## PCM - R 3 0 0

### DIGITAL AUDIO RECORDER

#### FEATURES

- ▶ The SBM Recording Function achieves an S/N ratio equivalent to that of a 20-bit system
- ▶ Offers Start ID, End ID, Skip ID, control on front panel
- ▶ Setup menu for preference section-set ID6, level sync threshold, CD-Q decode, and more.
- ▶ Error rate display can be selected on the display mode
- ▶ Coaxial and optical digital interface
- ▶ A/D and D/A monitoring modes
- ▶ Recording and playback in Long play mode
- ▶ Supplied Rack Mount Adapter for Rack Mounting

#### SPECIFICATIONS

Input / Out puts:  
 Analog I/O (Unbalanced)  
 RCA-pin -12dBu  
 Digital I/O  
 Optical, Coaxial (Pin-jack)  
 General:  
 Power requirement AC120V, 60Hz  
 (for the U.S. and Canada)  
 AC220 to 230V, 50/60Hz (for Europe)  
 Power consumption: 30W  
 Dimensions (W x H x D):  
 Appro x 432 x 122 x 325mm  
 Weight: Appro x 5.0 kg  
 Supplied Accessories:  
 Wireless remote commander  
 RM-D757 x 1  
 AC power code x 1  
 Operation manual x 1  
 Rack mount adapters x 2

*\*Design and specifications are subject to change without notice.*