

SONY



Incorporating Sony's legendary high-reliability 4 D.D. Mechanism, the PCM-R500 sets the standard for professional-use DAT. The Shuttle and Jog Dial offer outstanding operational ease, while extensive interface options and multiple menu modes meet a wide range of application needs.

NEW

PCM-R500

DIGITAL AUDIO RECORDER

FEATURES

- High-Reliability 4 D.D. Mechanical Transport**
Sony's legendary 4 D.D. Mechanism with 4 direct drive motors has been incorporated for a stable tape run. The PCM-R500 is also equipped with Auto Head Cleaning for improved sound quality.
- Easy Operation with Shuttle and Jog Dial**
The handy Shuttle/Jog Dial ensure easy system operation. Use the Shuttle for easy fast forward and rewind, or the Jog Dial for convenient AMS/Program Number.
- SBM Recording Function**
The SBM Recording Function achieves an S/N ratio equivalent to that of a 20-bit system.
- Set-Up Menu for Preference Selection**
Use the convenient set-up menu for setting ID6, level sync threshold, date and more.
- Built-in Din 8-Pin Parallel Remote Connector**
- Optional RM-D750 Wired Remote Commander**
- Wide Range of Audio Interface Options**
- R-Core Transformer for Reduced Leakage Flux**
Aiming for the highest possible sound quality, the PCM-R500 incorporates an R-Core Transformer for reduced leakage flux.
- CH1/CH2 Independent Recording Level Volume Controls**
The PCM-R500 includes independent Channel 1/Channel 2 recording level volume controls to eliminate cross talk.

SPECIFICATIONS

Input / Outputs:

Analog Input (Stereo)	XLR 3, Female
Reference level	+4dBu -12dBu
Unbalanced	RCA pin -12dBu
Output (Stereo)	XLR 3, Male
Reference level	+4dBu -12dBu
Unbalanced	RCA pin -12dBu
Digital Input (AES/EBU)	XLR 3, Female
Output	XLR 3, Male
Digital Input (Coaxial)	RCA Pin
Output	RCA Pin

Remote Interface:

REMOTE (8 pin)	DIN Connector (Parallel)
Optional remote commander input	Mini plug (Serial)

General:

Power Requirement	AC120V 60Hz for the U.S. and Canada AC220 to 230V 50/60Hz (for Europe)
Power consumption	34W
Dimensions (W x H x D)	Approx 40 x 145 x 300mm
Weight	Approx 7.2kg

Supplied Accessories:

- Wireless remote commander RM-D750 x 1
- AC power cord x 1
- Operation manual x 1

*Design and specifications are subject to change without notice.