

SONY®



Based on all the Features and Specs of the well-loaded PCM-R500; the PCM-R700 is also equipped with 4-Head Construction for Confidence monitoring.

NEW

PCM-R700

DIGITAL AUDIO RECORDER

F E A T U R E S

- **4-Head Construction for Confidence Monitoring**
- **High-Reliability 4 D.D. Mechanical Transport**
Sony's legendary 4 D.D. Mechanism with 4 direct drive motors has been incorporated for a stable tape run. The PCM-R700 is also equipped with Auto Head Cleaning for improved sound quality.
- **Easy Operation with Shuttle and Jog Dial**
The handy Shuttle/Jog Dial provides easy system operation. Use the Shuttle for easy fast forward and rewind, or the Jog Dial for convenient Automatic Music Sensor™/Program Number.
- **Super Bit Mapping® Recording Function**
The Super Bit Mapping Recording Function achieves a S/N ratio equivalent to that of a 20-bit system.
- **Set-Up Menu for Preference Selection**
Use the convenient set-up menu for setting ID6, level sync threshold, date and more.
- **8-Pin Din Parallel Remote Interface**
- **Optional RM-D750 Wired Remote Commander®**
- **Wide Range of Audio Interface Options**
- **Adjustable (0.5s-9.5s) Auto Fade on Front Panel**
- **CH1/CH2 Independent Recording Level Volume Controls**
The PCM-R700 includes independent Channel 1/Channel 2 recording level volume controls to eliminate cross talk.

S P E C I F I C A T I O N S

Input/Output:	
Analog input (Balanced)	XLR-3, Female
Reference level	+4dBu -12dBu
(Unbalanced)	RCA-pin -12dBu
output (Balanced)	XLR-3, Male
Reference level	+4dBu -12dBu
(Unbalanced)	RCA-pin -12dBu
Digital input (AES/EBU)	XLR-3, Female
output	BNC-3, Male
Digital input (Coaxial)	RCA Pin
output	RCA Pin

Remote Interface:
REMOTE (8-pin DIN Connector Parallel)
Optional Remote Commander input Miniplug (Serial)

General:	
Power requirement:	AC120V, 60Hz for the U.S. and Canada
Power consumption:	34W
Dimensions (W x H x D):	Approx 482 x 163 x 305mm
Weight:	Approx 7.4 kg

Supplied Accessories:
Wireless Remote Commander RM-D750 x 1
AC power cord x 1
Operation manual x 1

*Design and specifications are subject to change without notice.