# SONY

# Speaker Systems SRP-S730

The SRP-S730 Speaker System is designed for use as a floor foldback unit, or mounting on a wall or ceiling. It employs a 20 cm cone woofer and a horn tweeter to provide high quality sound output.



## Main Features -

1. Triangular-shaped enclosure for flexibility of application. Two different angles 35° or 45° can be chosen to the surface to mount.


For foldback use, the speaker axis is at an ideal 55° to the floor. Similarly, when ceiling mounted, the sound is directed downwards. Its shape also makes it suitable for corner mounting.

- 2. High reliability, with 110W rated input and 300W maximum input power. A protection circuit to prevent damage to the units from excessive input is included.
- 3. Clear and powerful sound, ideal for vocal reproduction and particularly suited to foldback and PA applications.
- 4. Neutrik Speakon connector for foldback use. Screw terminals for wall or ceiling fixed installation.
- 5. Optional MU-753S (black) bracket for ceiling mounting, MU-753M (black), bracket for wall / ceiling mounting. Fixing is with M5 bolts.



| Туре                      | 20 cm woofer and horn tweeter, bass-reflex |
|---------------------------|--|
| Rated impedance           | 8 ohms                                     |
| Rated input power         | 110 W (IEC 100 hours)                      |
| Max. input power          | 300 W                                      |
| Sensitivity               | 92 dB/W/m                                  |
| S.P.L. at rated input     | 112 dB                                     |
| Effective frequency range | 62 - 20,000 Hz (-10 dB)                    |
| Input terminals           | Neutrik Speakon NL-4MPR                    |
|                           | Screw terminal                             |
| Material of enclosure     | Particle board                             |
| Material of front grill   | Iron punching metal                        |
| Color of grill            | Black                                      |
| Operating temperature     | -10 to +50°C                               |
| Storage temperature       | -20 to +60°C                               |
| Dimensions                | Approx. 280(W) x 450(H) x 310(D) mm        |
|                           | 11 1/8(W) x 17 3/4(H) x 12 1/4(D) inch     |
| Mass                      | Approx. 7.5 kg                             |
| optional accessories      | For SRP-S730:                              |
|                           | MU-753S ceiling mounting black bracket     |
|                           | MU-753M wall / ceiling mounting black      |
|                           | bracket                                    |

Specifications \_\_\_\_\_



Unit: mm

### Distributed by

©1998 Sony Corporation. All right reserved. Reproduction in whole in part without written permission is prohibited. Features and specifications are subject to change without notice. All non-metric weights and measures are approximate. Sony is a registered trademark of Sony Corporation. Neutrik Speakon is a registered trademark of Neutrik Ltd. All other trademarks are property of their respective owners.

> Sony Corporation Printed in Japan © SONY

#### MK7161V2AUT99JUN