SLV-D281P/D380P

SERVICE MANUAL

US Model





Photo: SLV-D380P

SPECIFICATIONS

System

Semiconductor laser

Format

VHS NTSC standard

Video recording system

Rotary head helical scanning FM system

Double azimuth four heads

Video signal

NTSC color, EIA standards

Tape speed

SP: 33.35 mm/s (1 3/8 inches/s)

EP: 11.12 mm/s (7/16 inches/s)

LP: 16.67 mm/s (11/16 inches/s),

playback only

Maximum recording/playback time

8 hrs. in EP mode (with T-160 tape)

Rewind time

Approx. 2 min (with T-120 tape)

Inputs and outputs

LINE IN 1 and LINE-2 IN

VIDEO IN, phono jack (1 each)

Input signal: 1 Vp-p, 75 ohms, unbalanced, sync

negative

AUDIO IN, phono jacks (2 each)

Input level: 327 mVrms

Input impedance: more than 47 kilohms

LINE OUT

VIDEO OUT, phono jack (1)

Output signal: 1 Vp-p, 75 ohms, unbalanced, sync

AUDIO OUT, phono jacks (2)

Standard output: 327 mVrms

Load impedance: 47 kilohms

Output impedance: less than 10 kilohms

DIGITAL OUT

COAXIAL, phono jack

Output signal: 0.5 Vp-p, 75 ohms

COMPONENT VIDEO OUT (Y, Pb, Pr) Phono jack

Y: 1.0 Vp-p/Pb, Pr: 0.7 Vp-p, 75 ohms

Timer section

Ouartz locked

Timer indication

12-hour cycle

Timer setting

8 programs (max.)

General

Power requirements

120 V AC, 60 Hz

Power consumption 25 W

Power back-up

Back-up duration: 0 min

Operating temperature

5°C to 40°C (41°F to 104°F)

Storage temperature

-20°C to 60°C (-4°F to 140°F)

Operating humidity

25% to 80%

Dimensions including projecting parts and controls

Approx. $430 \times 85 \times 287 \text{ mm}$

(Approx. $17 \times 3 \frac{3}{8} \times 11 \frac{3}{8}$ inches)

Approx. 3.5 kg (Approx. 7.7 lbs)

Supplied accessories

Remote commander (1)

Size AA (R6) batteries (2)

Audio/video cord (1)

Design and specifications are subject to change without







DVD PLAYER/ VIDEO CASSETTE RECORDER



SLV-D281P/D380P

REPAIR PARTS LIST

 Ref. No.
 Part No.
 Description
 Remarks

 ACCESSORIES & PACKING MATERIALDS

3-093-964-11 MANUAL, INSTRUCTION

(ENGLISH, SPANISH) (D380P)

3-093-965-11 MANUAL, INSTRUCTION

(ENGLISH, SPANISH) (D281P)

9-885-111-07 COMMANDER (RMT-V504A), (TYPE)