

# CCP SPECIFICATION TABLE

SPECIFICATIONS	STEREO		MONO	
	CCP-2310F/2410F	CCP-2300/2400	CCP-1310F/1410F	CCP-1300/1400
COPY SPEED	30 ips	30 ips	30 ips	30 ips
REWIND TIME (C-60)	~40 seconds	~40 seconds	~40 seconds	~40 seconds
BANDWIDTH	40Hz-10kHz	40Hz-12.5kHz	40Hz-10kHz	50Hz-10kHz
EQUALIZATION	Type 1 (normal bias)	Type 1 (normal bias)	Type 1 (normal bias)	Type 1 (normal bias)
SIG/NOISE	>49 dB	>50 dB	>52 dB	>52 dB
CROSSTALK REJECTION (1kHz at 0db)	>53 dB between Side A and B	>52 dB between Side A and B	>52 dB between Side A and B	>52 dB between Side A and B
TOTAL HARMONIC DISTORTION (accumulative total)	<3%	<3%	<3%	<3%
WOW/FLUTTER (accumulative total)	<0.23%	<0.23%	<0.23%	<0.23%
PLAY/RECORD HEADS	4 Track, 4 Channel Glass Bonded Ferrite	4 Track, 4 Channel Hexalloy	2 Track, 2 Channel Glass Bonded Ferrite	2 Track, 2 Channel Hexalloy
FRASE HEADS	Yes	Yes	Yes	Yes
POWER REQUIREMENTS	120 VAC, 60 Hz	120 VAC, 60 Hz	120 VAC, 60 Hz	120 VAC, 60 Hz
POWER CONSUMPTION	0.67A	0.74A	0.6A	0.6A
CAPSTAN MOTOR	1) DC Brushless	1) DC Brushless	1) DC Brushless	1) DC Brushless
REEL MOTOR	8) DC	8) DC	8) DC	8) DC
WEIGHT	22 lb., 8 oz.	22 lb., 8 oz.	21 lb., 10 oz.	21 lb., 10 oz.
DIMENSIONS				
Width: (in.)	13	13	13	13
Height: (in.)	6 3/8	6 3/8	6 3/8	6 3/8
Depth: (in.)	15 1/8	15 1/8	15 1/8	15 1/8
MACHINE WARRANTY (parts/labor)	1 Year	1 Year	1 Year	1 Year
HEAD WARRANTY	2 Years	1 Year	2 Years	1 Year
EXPANSION UNIT CAPABILITY	10 units for 43 Simultaneous Copies	10 units for 43 Simultaneous Copies	10 units for 43 Simultaneous Copies	10 units for 43 Simultaneous Copies

© 1998 Sony Electronics Inc.  
 Reproduction in whole or in part without written permission is prohibited. All rights reserved.

Features and specifications subject to change without notice. Sony is a trademark of Sony.

## SONY

Sony Electronics Inc.  
 One Sony Drive  
 Park Ridge, NJ 07656

1-800-472-SONY, EXT. CCP  
[www.sony.com/professional](http://www.sony.com/professional)

ES-022-B  
 Printed in USA 4-98