SONY

DYNAMIC MICROPHONE



OUTLINE

The Sony F-112 is a new highquality dynamic microphone, specifically designed for field production and newsgathering applications. Equipped with a newly developed omni-directional microphone capsule, the F-112 achieves highly sensitive and clear voice pick-up from all directions. Its robust body construction enables stable sound acquisition even in the harshest of environments encountered in the field. In addition, the F-112 offers a well thought-out ergonomic design which provides a stable grip, as well as optimized balance when combined with the wireless plug-on transmitter included in the Sony UWP-C3 package – features essential for conducting smooth interviews. With its high performance, durability, and sophisticated design, the F-112 microphone is an ideal choice for demanding voice pick-up applications.

FEATURES

Superior Sound Quality

Incorporating a newly developed omni-directional microphone capsule, the F-112 delivers a high sensitivity of -54 dB (0 dB=1 V/Pa.), allowing clear voice pick-up from any direction.

Flat-and-wide Frequency Response

The F-112 has a flat-and-wide frequency response (60 Hz to 17 kHz), which provides smooth and natural sound reproduction.

Robust and Sophisticated Design

The F-112 has been designed with special considerations for heavy-duty field use. The body is made of metal, offering a high level of durability to withstand severe conditions encountered in demanding sound pick-up scenarios. In addition, its well-balanced design allows comfortable handling when used with the plug-on transmitter included in the Sony UWP-C3 package.




F-112 with an optional plug-on transmitter included in the UWP-C3 package

SPECIFICATIONS

	F-112
Capsule type	Dynamic
Directivity	Omni-directional
Frequency response	60 Hz to 17 kHz
Sensitivity (at 1 kHz)	-54 dB ⁺¹ ±3 dB
Output impedance (at 1 kHz)	400 Ω ±20%
Dimensions	ø20/38 x 190 mm (ø13/16 (handle), ø1 1/2 (head) x 7 1/2 inches)
Mass	180 g (6 oz)
Supplied accessories	Operating instructions (x1)

*1 0 dB=1 V/Pa., at 1 kHz



Frequency Response Characteristics

OPTIONAL ACCESSORY



UHF Synthesized Wireless Microphone System

- Consists of a plug-on transmitter and portable tuner
- Suitable for a wide range of applications, from news gathering and interviews to talk shows and conferences
- The plug-on transmitter converts a wired microphone to a wireless microphone via an XLR connector
- The portable tuner is supplied with a microphone stand adaptor, screw adaptor, shoe-mount adaptor for mounting on a camcorder, belt clip and microphone cables (3-pole mini-plug/XLR-type, 3-pole mini-plug/stereo mini-plug)

Distributed by

©2005 Sony Corporation. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. All non-metric weights and measurements are approximate. Sony is a registered trademark of Sony Corporation.