

SONY

> Sony Financial Services



ECM530 Tabletop Microphone

\$420.00 U.S. List Price

Description

Tabletop Microphone. Ideal for conference or lecture application. Flexible gooseneck design, "AA" Battery and Phantom Power operation, matte black finish, noise-isolated base, inconspicuous wiring through the back of the base.

Highlights

- ❑ Ideally suited for conference and lecture applications
- ❑ Compact and slim table-top microphone
- ❑ 2-way powering-AA-size battery or external power supply

Specifications

Specification	Detail
❑ Capsule type	Electret Condenser
❑ Directivity	UNI
❑ Power supply	
❑ Battery	1.5
❑ Frequency response (Hz)	70 - 18,000
❑ Dynamic range (dB)	equal to or greater than 95
❑ Signal-to-noise ratio (dB) (A weighted, 1kHz, 1Pa.	equal to or greater than 63
❑ Induction noise from ext. magnetic field (OdB = 20	5
❑ Ext.Power	DC 14-48
❑ Sensitivity	-49.0 ± 2.0(dB)
❑ Inherent noise (OdB = 20μPa.) (dB SPL)	equal to or less than 31
❑ Effective output level at 1kHz (0dBm=1mW/1 P	-46.8(dBm)
❑ Wind noise (OdB = 20μPa.)	55(dB SPL)
❑ Output impedance at 1kHz (balanced)	150 ohms

☐ Max. input sound pressure level (OdB = 20μ 126(dB SPL)

☐ Battery IECR6

--

